



























TECH CONTROLLERS



2024
PRICE LIST

EU

TABLE OF CONTENTS

| | | |
|---|---|-----------|
| Wireless system for wireless electric actuators control Via internet |  | 4 |
| Smart home system- Sinum - heating solutions |  | 6 |
| Universal floor heating system with internet - 4 series |  | 10 |
| Universal floor heating system with internet - 4X series |  | 12 |
| Wired floor heating system - 5 series |  | 16 |
| Wireless floor heating system with internet - 8 series |  | 18 |
| Wired/ Wireless floor heating system with internet - 9 series |  | 21 |
| Wired floor heating system - 10 series |  | 24 |
| Wired floor heating system - X series |  | 26 |
| Wired floor heating system - 12 series |  | 29 |
| Wired room regulators two-state (on/off) |  | 33 |
| Wireless room regulators two-state (on/off) |  | 34 |
| Wired room regulators with RS communication |  | 35 |
| Wireless room regulators with RS communication |  | 35 |
| Room regulators for 55mm frame systems |  | 35 |
| Regulators for gas boilers |  | 36 |
| Air cleaning and sterilizing |  | 36 |
| Installation controllers |  | 37 |
| Solar installation controllers |  | 38 |
| Pump controllers |  | 38 |
| Charging boiler controllers |  | 38 |
| Boiler with feeder controllers |  | 39 |
| Fireplace controllers |  | 39 |
| Additional modules / accessories |  | 40 |
| Additional sensors |  | 41 |
| Fans |  | 42 |

All prices are net value

In case of lack of casing colour selection color will be chosen randomly.

(Only for product with different colour variants)

Legend:

| PRODUCT PHOTO | PRODUCT DESCRIPTION AND NAME, FUNCTIONS | | | |
|---------------|---|------------------|----------|-----------|
| | ADDITIONAL INFORMATION | CATALOGUE NUMBER | EAN CODE | COLOUR |
| | | | | NET PRICE |


EU-WiFi 8S WIFI MODULE FOR THERMOELECTRIC ACTUATORS

Functions: Control of up to 8 heating zones using:

- built-in temperature sensor
- 1 wired room temperature sensor EU-C-7p included
- possibility of connecting up to 8 system wireless sensors or wireless room regulators
- relay output NO/NC (to control the heating device, when heat needed)
- possibility of connecting up to 6 pcs of wireless electric actuators STT-868 or STT-869 for each zone

Maintain of the system via web app: www.emodul.eu

WG.20.0059
5902479660998
246 €

EU-WiFi 8S p WIFI MODULE FOR THERMOELECTRIC ACTUATORS (FLUSH-MOUNTABLE)

Functions: Control of up to 8 heating zones using:

- possibility of connecting up to 8 system wireless sensors or wireless room regulators
- relay output NO/NC (to control the heating device, when heat needed)
- possibility of connecting up to 6 pcs of wireless electric actuators STT-868 or STT-869 for each zone
- 1 wireless temperature sensor EU-C-mini included

Maintain of the system via web app: www.emodul.eu

WHILE STOCKS LAST
WG.20.0141
5902479664194
246 €

EU-16S WiFi WIFI ROOM REGULATOR FOR CONTROL WIRELESS ELECTRIC ACTUATORS (FLUSH-MOUNTABLE)

Functions: Control of **max 16 zones** by means: built-in temperature sensor or by connecting additional **15** system wireless sensors or wireless room regulators. For each zone it is possible to connect up to 6pcs STT-868 or STT-869 wireless thermoelectric actuators. Each zone can have its own operation mode: constant temperature, temperature with time limitation or 6 different fully adjustable schedules. Room regulators displays: temperature, date, hour, alarm clock. Controller has display adjusting its brightness during the day. It is possible to update the room regulator via USB port. Easy installation in an electrical box (ø60mm). Power supply: 230V 50Hz, 4,3" colour touchscreen, **WiFi connection**,

Maintain of the system via web app: www.emodul.eu

WHILE STOCKS LAST
WG.20.0038
5902479661742
417 €
WG.20.0039
5902479662244
ROOM REGULATORS AND TEMPERATURE SENSORS - BATTERY, WIRELESS

EU-C-8r WIRELESS ROOM TEMPERATURE SENSOR

Power: 2xAAA batteries

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.03.0079
5902479661056
38 €
WG.03.0082
5902479662084

EU-C-mini WIRELESS ROOM TEMPERATURE SENSOR

Dimensions: 37mm x 37mm x 16mm

WHILE STOCKS LAST
WG.03.0085
5902479662817
37 €

EU-CL-mini WIRELESS ROOM TEMPERATURE SENSOR IN HERMETIC CASING

MEETS THE IP64 STANDARD

Dimensions: 44,3mm x 44,3mm x 17mm

WG.03.0084
5902479661636
43 €

EU-C-8zr WIRELESS OUTSIDE TEMPERATURE SENSOR

Power: 2xAAA batteries

WG.03.0083
5902479661063
39 €

EU-R-8b WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0188
5902479661070
49 €
WG.11.0192
5902479662091

EU-R-8x WIRELESS REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LCD display, 2xAAA batteries, no backlit, mechanical buttons

WG.11.0734
5902479665924
48 €
WG.11.0760
5902479666099

EU-R-8b PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0195
5902479663647
66 €
WG.11.0196
5902479663654

EU-R-8s PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, 2xAAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0644
5902479664385
100 €
WG.11.0696
5902479664378



EU-R-8pb PLUS BWIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR (FLUSCH MOUNTABLE)

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, powered 2xAAA Batteries, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WHILE STOCKS LAST

WG.11.0699
WG.11.0700

5902479665009
5902479665016

108 €

ROOM REGULATORS - 230V, WIRELESS



EU-R-8z WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LED display, power supply: 230V 50Hz to 5V included

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0202
WG.11.0203

5902479661087
5902479662107

66 €



EU-F-8z WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR FOR 55MM FRAME SYSTEMS

Functions: room temperature control, heating program with time limit, additional control based on floor temperature (in case of using NTC floor sensor - not included).

Equipment: built-in room temperature and humidity sensor, LCD display, no backlit, 230V powered, Flush mountable in electrical box (ø60mm), no backlit,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0634
WG.11.0686

5902479664408
5902479664415

89 €



EU-R-8pz PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR (FLUSCH MOUNTABLE)

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, powered 230V, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0701
WG.11.0702

5902479665030
5902479665023

136 €

ADDITIONAL MODULES AND ACTUATORS



EU-C-2N WINDOW SENSOR

Functions: wireless communication, window opening signal, heating control, compact in size, long-life battery, discreet design.

Power: EVE ER14250 S battery

RAL 9010 - white
RAL 7016 - antracite
RAL 8017 - brown
RAL 8003 - golden oak

WG.03.0070
WG.03.0069
WG.03.0071
WG.03.0068

5902479661339
5902479664248
5902479664255
5902479664262

45 €



EU-MW-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MW-1) or voltage relay (EU-MW-1-230V), operation in manual mode, wireless communication with main controller or temperature sensor (master/slave mode), in case of loss of communication, the contact is switched off. 4 LEDs indicating: communication, power, manual mode, contact status

EU-MW-1
EU-MW-1-230V

WG.05.0114
WG.05.0116

5902479661346
5902479662374

114 €



EU-MWN-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MWN-1) or voltage relay (EU-MWN-1-230V), wireless communication with main controller (slave mode), in case of loss of communication, the contact is switched off

MWN-1
MWN-1-230V

WG.05.0197
WG.05.0117

5902479664507
5902479664392

114 €



EU-RP-4 SIGNAL REPEATER

The signal repeater is a small electronic device that increases the range of wireless communication between devices without the need for additional cables. Thanks to the device, controller which are away from main unit will be able to establish a stable connection

WG.05.0140

5902479662824

114 €



EU-G-X WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S p, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAA 1,5V batteries. **Available thread M28x1,5 adapter**

WG.12.0045

5902479665054

97 €



STT-869 WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S p, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAA 1,5V batteries. new design, registration button built on the front of actuator, **Available thread M28x1,5 adapter**

WG.12.0016

5902479662381

97 €



TECH
CONTROLLERS



EH-01 SINUM CENTRAL

Functions: EH-01 is a device which collects and processes information from external devices and executive modules, giving you the opportunity to view and change their operating status via your home network or CLOUD services. The device also allows you to create automations involving connected devices as well as data collected from them. It is also possible to create scenes and schedules. EH-01 cares for the comfort and safety of your entire family 24/7.

WTP / TECH SBUS

WG.23.0005
WG.23.0024

5902479665047
5902479665115

468 €

ADDITIONAL MODULES WIRED (M) OR WIRELESS - SINUM



PS-10 230 / PS-10m 230 WIRELESS CONTROLLER FOR THERMOSTATIC ACTUATORS

Functions:

- possibility of controlling up to 50 thermostatic actuators
- one 230V output for pump
- voltage-free contact (e.g. for controlling the heating device)
- 2x voltage-free input

PS-10 230
PS-10m 230

WTP
TECH SBUS

WG.23.0044
WG.23.0054

5902479665801
5902479665702

165 €



PS-02 DIN RAIL RELAY

Functions:

- 2x voltage input
- 2x voltage-free output

WTP

WG.23.0003

5902479664781

60 €



PS-06m DIN RAIL RELAY

Functions:

- 6x voltage-free output

TECH SBUS

WG.23.0047

5902479666006

94 €



PS-08 DIN RAIL RELAY

Functions:

- 8x voltage-free output

WTP

WG.23.0004

5902479664798

93 €



PS-08 230 / PS-08m 230 DIN RAIL RELAY

Functions:

- 8x voltage output 230V

PS-08 230
PS-08m 230

WTP
TECH SBUS

WG.23.0020
WG.23.0046

5902479664934
5902479666013

96 €
101 €

DEDICATED SINUM ROOM REGULATORS - RS 485



RS-1 DEDICATED WIRED ROOM REGULATOR FOR SINUM

Functions: room temperature control, RS485 wired communication, 24V DC powered

Equipment: built-in room temperature sensor, humidity sensor, LCD display, no backlight, mechanical buttons

TECH SBUS

WG.23.0055

5902479665931

66 €



RS-2 DEDICATED WIRED ROOM REGULATOR FOR SINUM

Functions: room temperature control, RS485 wired communication, power 24V DC

Equipment: built-in room temperature sensor, humidity sensor, LCD display, no backlight, touchable buttons

* White or black casing. In case of lack of colour selection color will be chosen randomly.

TECH SBUS

WG.23.0056
WG.23.0059

5902479665948
5902479665979

77 €



RS-3 DEDICATED WIRED ROOM REGULATOR FOR SINUM

Functions: room temperature control, additional control based on floor temperature (if floor sensor is used), RS485 wired communication, power 24V DC

Equipment: built-in room temperature sensor, humidity sensor, LCD display with temporary backlight

* White or black casing. In case of lack of colour selection color will be chosen randomly.

TECH SBUS

WG.23.0057
WG.23.0060

5902479665955
5902479665986

84 €



FR-S2 DEDICATED WIRED ROOM REGULATOR FOR SINUM FOR 55MM FRAME SYSTEMS

Functions: room temperature control, additional control based on floor temperature (if floor sensor is used), RS485 wired communication, power 24V DC

Equipment: built-in room temperature sensor, humidity sensor, LCD display, no backlight, flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

TECH SBUS

WG.23.0052
WG.23.0064

5902479665894
5902479666044

75 €



CP-04m WIRED CONTROL PANEL FOR SINUM

Functions: The CP-04 control panel is a multi-tasking device. Thanks to it, we can display the current weather forecast, check the temperature in the room in which it is installed (has the possibility of connecting an air temperature sensor and a floor temperature sensor) and set shortcuts to favorite scenes. The panel therefore functions as a weather indicator, temperature controller and scene switch. All this is controlled from a 4-inch color touch screen, RS485 wired communication, power 24V DC

* White or black casing. In case of lack of colour selection color will be chosen randomly.

TECH SBUS

WG.23.0063

5902479666037

306 €

SYSTEM ROOM REGULATORS AND TEMPERATURE SENSORS - BATTERY, WIRELESS



EU-C-8r WIRELESS ROOM TEMPERATURE SENSOR

Power: 2xAAA batteries

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.03.0079

5902479661056

38 €

WG.03.0082

5902479662084



EU-C-mini WIRELESS ROOM TEMPERATURE SENSOR

Dimensions: 37mm x 37mm x 16mm

WHILE STOCKS LAST

WG.03.0085

5902479662817

37 €



EU-CL-mini WIRELESS ROOM TEMPERATURE SENSOR IN HERMETIC CASING

MEETS THE IP64 STANDARD

Dimensions: 44,3mm x 44,3mm x 17mm

WG.03.0084

5902479661636

43 €



EU-C-8zr WIRELESS OUTSIDE TEMPERATURE SENSOR

Power: 2xAAA batteries

WG.03.0083

5902479661063

39 €



EU-R-8b WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0188

5902479661070

49 €

WG.11.0192

5902479662091



EU-R-8x WIRELESS REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LCD display, 2xAA batteries, no backlit, mechanical buttons

WG.11.0734

5902479665924

48 €

WG.11.0760

5902479666099



EU-R-8b PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0195

5902479663647

66 €

WG.11.0196

5902479663654



EU-R-8s PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, 2xAAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0644

5902479664385

100 €

WG.11.0696

5902479664378



EU-R-8pb PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR (FLUSH MOUNTABLE)

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, powered 2xAAA Batteries, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0699

5902479665009

108 €

WG.11.0700

5902479665016

WHILE STOCKS LAST

ROOM REGULATORS - 230V, WIRELESS



EU-R-8z WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LED display, power supply: 230V 50Hz to 5V included

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0202

5902479661087

66 €

WG.11.0203

5902479662107



TECH
CONTROLLERS



EU-F-8z WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR FOR 55MM FRAME SYSTEMS

Functions: room temperature control, heating program with time limit, additional control based on floor temperature (in case of using NTC floor sensor - not included),

Equipment: built-in room temperature and humidity sensor, LCD display, no backlight, 230V powered, Flush mountable in electrical box (ø60mm), no backlight,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0634
WG.11.0686

5902479664408
5902479664415

89 €



EU-R-8pz PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR (FLUSH MOUNTABLE)

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlight, powered 230V, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0701
WG.11.0702

5902479665030
5902479665023

136 €

ADDITIONAL MODULES



EU-C-2N WINDOW SENSOR

Functions: wireless communication, window opening signal, heating control, compact in size, long-life battery, discreet design.

Power: EVE ER14250 S battery

RAL 9010 - white
RAL 7016 - antracite
RAL 8017 - brown
RAL 8003 - golden oak

WG.03.0070
WG.03.0069
WG.03.0071
WG.03.0068

5902479661339
5902479664248
5902479664255
5902479664262

45 €



EU-MW-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MW-1) or voltage relay (EU-MW-1-230V), operation in manual mode, wireless communication with main controller or temperature sensor (master/slave mode), in case of loss of communication, the contact is switched off. 4 LEDs indicating: communication, power, manual mode, contact status

EU-MW-1
EU-MW-1-230V

WG.05.0114
WG.05.0116

5902479661346
5902479662374

114 €



EU-MWN-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MWN-1) or voltage relay (EU-MWN-1-230V), wireless communication with main controller (slave mode), in case of loss of communication, the contact is switched off

MWN-1
MWN-1-230V

WG.05.0197
WG.05.0117

5902479664507
5902479664392

114 €



EX-01 EXTENDER SYGNAŁ

Functions: Thanks to the Sinum extender, you will extend the range of the wireless system. The extender connects to wireless devices of the Sinum system and transmits data via WiFi to the EH-01 control device.. power 230V AC

WTP

WG.23.0006

5902479664699

131 €



EHI-2 MIXING VALVE MODULE

Functions: The EHI-2 mixing valve module allows you to extend the Sinum system to support 2 mixing valves. The controller has voltage outputs to operate 2 mixing valves (open/close), 2 pumps dedicated to valves and 1 additional pump. In addition, it has a voltage-free contact and the ability to connect an RS regulator or two 2-state regulators. The device can also work independently without being connected to the Sinum control device. Communication with the Sinum EH-01 control device is done by wire via the TECH RS bus.

TECH RS

WG.23.0035

5902479665641

236 €



EU-G-X WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S p, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAAA 1.5V batteries. **Available thread M28x1,5 adapter**

WG.12.0045

5902479665054

97 €



STT-869 WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S p, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAAA 1.5V batteries. new design, registration button built on the front of actuator, **Available thread M28x1,5 adapter**

WG.12.0016

5902479662381

97 €



STT-230/2 THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28x1,5 screw thread, Stroke: 3,5 mm, Class: IP40. Opening time: under 5 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5
M28 x 1,5

WG.01.0050
WG.01.0051

5902479660691
5902479661490

34 €



STT-230/2 T THERMOELECTRIC ACTUATOR
ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28 x 1,5 screw thread, Class - IP45. Opening time: under 3,5 min. Stroke - 3,7mm,Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5

WG.01.0053

5902479663630

24 €

M28 x 1,5

WG.01.0054

5902479665597

27 €



STT-230/2 M THERMOELECTRIC ACTUATOR
ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 screw thread, Class - IP42. Opening time: under 4 min. to 3mm, Stroke - 5mm,Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5

WG.01.0052

5902479665108

24 €

TECH
CONTROLLERS

 **Sinum**



Your home in tune with you.



Heating



Lighting



Safety
and quality



Control
of roller shutters
and awnings

Get to know our solutions at **sinum.eu**

UNIVERSAL FLOOR HEATING SYSTEM WITH INTERNET - 4 SERIES



EU-L-4 WiFi WIRELESS CONTROLLER FOR THERMOSTATIC ACTUATORS (8 SECTIONS)

- Functions:**
- control of **4 voltage outputs** by 4 wired temperature sensors, or system wireless room regulators or wireless temperature sensors
 - voltage-free contact (for controlling additional heating device)
 - **possibility of controlling the system via Internet (eModul app)**
 - possibility of control of **8 zones**:
 - 4 zones are controlled by system wireless temperature sensors or wireless room regulators
 - 4 zones with voltage outputs are controlled by 4 wired temperature sensors **EU-C-7p** or by systems wireless temperature sensors or wireless room regulators for each zone there is possibility of connecting 4 wireless electric actuators **STT-868**, or **STT-869**
 - possibility of connecting **4 wired floor NTC** or **8 wireless** - **EU-C-8f**, floor sensors
 - possibility of connecting **8 wireless executive modules** **EU-MW-1** or **EU-MW-1-230V**
 - software update via **USB**

WHILE STOCKS LAST

WG.20.0044

5902479662367

273 €

TEMPERATURE SENSORS - WIRED



EU-C-7p WIRED ROOM TEMPERATURE SENSOR

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.03.0072

5902479661032

22 €

WG.03.0075

5902479662060

SYSTEM ROOM REGULATORS AND TEMPERATURE SENSORS - BATTERY, WIRELESS



EU-C-8r WIRELESS ROOM TEMPERATURE SENSOR

Power: 2xAAA batteries

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.03.0079

5902479661056

38 €

WG.03.0082

5902479662084



EU-C-8f WIRELESS FLOOR TEMPERATURE SENSOR

Floor temperature sensor NTC type, power supply: 2x AAA batteries

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.03.0076

5902479661643

43 €

WG.03.0078

5902479662220

WHILE STOCKS LAST



EU-C-mini WIRELESS ROOM TEMPERATURE SENSOR

Dimensions: 37mm x 37mm x 16mm

WHILE STOCKS LAST

WG.03.0085

5902479661636

37 €



EU-CL-mini WIRELESS ROOM TEMPERATURE SENSOR IN HERMETIC CASING

MEETS THE IP64 STANDARD

Dimensions: 44,3mm x 44,3mm x 17mm

WG.03.0084

5902479662817

43 €



EU-C-8zr WIRELESS OUTSIDE TEMPERATURE SENSOR

Power: 2xAAA batteries

WG.03.0083

5902479661063

39 €



EU-R-8b WIRELESS REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LCD display, 2xAAA batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0188

5902479661070

49 €

WG.11.0192

5902479662091



EU-R-8x WIRELESS REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LCD display, 2xAA batteries, no backlit, mechanical buttons

WG.11.0734

5902479665924

48 €

WG.11.0760

5902479666099



EU-R-8b PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, temperature control on the basis of floor temperature (in case of using NTC floor sensor - not included), LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0195

5902479663647

66 €

WG.11.0196

5902479663654

WHILE STOCKS LAST



EU-R-8s PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, 2xAAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0644

5902479664385

100 €

WG.11.0696

5902479664378



EU-R-8pb PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, powered 2xAAA batteries, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0699
WG.11.0700

5902479665009
5902479665016

108 €

ROOM REGULATORS - 230V, WIRELESS



EU-R-8z WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LED display, power supply: 230V 50Hz to 5V included

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0202
WG.11.0203

5902479661087
5902479662107

66 €



EU-F-8z WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR FOR 55MM FRAME SYSTEMS

Functions: room temperature control, heating program with time limit, additional control based on floor temperature (in case of using NTC floor sensor - not included), **Equipment:** built-in room temperature and humidity sensor, LCD display, no backlit, 230V powered, Flush mountable in electrical box (ø60mm), no backlit,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0634
WG.11.0686

5902479664408
5902479664415

89 €



EU-R-8pz PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, powered 230V, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0701
WG.11.0702

5902479665023
5902479665030

136 €

ADDITIONAL MODULES AND ACTUATORS



EU-C-2N WINDOW SENSOR

Functions: wireless communication, window opening signal, heating control, compact in size, long-life battery, discreet design.

Power: EVE ER14250 S battery

RAL 9010 - white
RAL 7016 - antracite
RAL 8017 - brown
RAL 8003 - golden oak

WG.03.0070
WG.03.0069
WG.03.0071
WG.03.0068

5902479661339
5902479664248
5902479664255
5902479664262

45 €



EU-MW-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MW-1) or voltage relay (EU-MW-1-230V), operation in manual mode, wireless communication with main controller or temperature sensor (master/slave mode), in case of loss of communication, the contact is switched off 4 LEDs indicating: communication, power, manual mode, contact status

EU-MW-1
EU-MW-1-230V

WG.05.0114
WG.05.0116

5902479661346
5902479662374

114 €



EU-MWN-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MWN-1) or voltage relay (EU-MWN-1-230V), wireless communication with main controller (slave mode), in case of loss of communication, the contact is switched off

EU-MWN-1
EU-MWN-1-230V

WG.05.0197
WG.05.0117

5902479664507
5902479664392

114 €



EU-RP-4 SIGNAL REPEATER

The signal repeater is a small electronic device that increases the range of wireless communication between devices without the need for additional cables. Thanks to the device, controller which are away from main unit will be able to establish a stable connection

WG.05.0140

5902479662824

114 €



EUG-X WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S p, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 EU-L-X WiFi, EU-L-12, controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAA 1,5V batteries. new design, hidden registration button. **Available thread M28x1,5 adapter**

WG.12.0045

5902479665054

97 €



STT-869 WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S p, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 EU-L-X WiFi, EU-L-12, controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAA 1,5V batteries. new design, registration button built on the front of actuator, **Available thread M28x1,5 adapter**

WG.12.0016

5902479662381

97 €



STT-230/2 THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28x1,5 screw thread, Stroke: 3,5 mm, Class: IP40. Opening time: under 5 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5
M28 x 1,5

WG.01.0050
WG.01.0051

5902479660691
5902479661490

34 €



STT-230/2 T THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28 x 1,5 screw thread, Class - IP45. Opening time: under 3,5 min. Stroke - 3,7mm, Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5
M28 x 1,5

WG.01.0053
WG.01.0054

5902479663630
5902479665597

24 €
27 €



STT-230/2 M THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 screw thread, Class - IP42. Opening time: under 4 min. to 3mm, Stroke - 5mm, Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5

WG.01.0052

5902479665108

24 €



TECH
CONTROLLERS

UNIVERSAL FLOOR HEATING SYSTEM WITH INTERNET - 4X SERIES

EU-L-4X WiFi WIRED/WIRELESS CONTROLLER FOR THERMOSTATIC ACTUATORS (8 SECTIONS) WITH WIFI

- Functions:**
- management of 8 radiator zones or 4 radiator zones and 4 floor zones (with built-in 4 voltage relay outputs)
 - management of 8 floor zones when connecting the **ML-4X WiFi** extension module (additional 4 voltage relay outputs)
 - control of 8 zones using dedicated wired controllers or wireless system controllers or temperature sensors
 - control of 4 zones using wired temperature sensors C-7p
 - control of floor temperature sensor C-8f
 - external temperature sensor C-8zr support and weather control
 - communication with dedicated devices using the **TECH SBUS** protocol
 - one 230V output for a pump
 - voltage-free relay (to control an additional heating device)
 - possibility of controlling wireless actuators **STT-869/6-X** (the maximum of 6 per zone)
 - in each zone, it is possible to install up to 6 wireless **EU-C-2n** window opening sensors
 - possibility of connecting 6 executive modules **EU-MW-1** or **EU-MW-1/230**
 - possibility of connecting **EU-i-1** or **EU-i-1m** valve module
 - built-in WiFi module
 - the ability to control the installation via the Internet, eModul application
 - heating/cooling function**
 - software update via USB



NEW !

WG.20.0191

5902479665900

282 €

EU-ML-4X WiFi IS AN EXTENSION OF THE EU-L-12 SYSTEM

- Functions:**
- module with 4 additional voltage relay outputs extending the capabilities of the EU-L-4X WiFi controller by adding 4 extra floor zones
 - the module does not operate independently



NEW !

WG.20.0196

5902479666068

71 €

ROOM REGULATORS AND SENSORS POWERED FROM MAIN CONTROLLER - DEDICATED RS 485

EU-R-X DEDICATED WIRED ROOM REGULATOR FOR EU-L-X WIFI CONTROLLER

- Functions:** room temperature control, additional control based on floor temperature (if floor sensor is used), RS485 wired communication **4-wire / no batteries**

- Equipment:** built-in room temperature sensor, LCD display, no backlight, mechanical buttons



WG.11.0737

5902479665627

48 €

WG.11.0759

5902479665634

EU-R-12b DEDICATED WIRED ROOM REGULATOR FOR EU-L-X WIFI CONTROLLER

- Functions:** room temperature control, additional control based on floor temperature (if floor sensor is used), RS485 wired communication **4-wire / no batteries**

- Equipment:** built-in room temperature sensor, humidity sensor, LCD display, no backlight

- * White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.11.0703

5902479664569

65 €

WG.11.0704

5902479664576

EU-R-12s DEDICATED WIRED ROOM REGULATOR FOR EU-L-X WIFI CONTROLLER

- Functions:** room temperature control, additional control based on floor temperature (if floor sensor is used), RS485 wired communication **4-wire / no batteries**

- Equipment:** built-in room temperature sensor, humidity sensor, LCD display with temporary backlight

- * White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.11.0705

5902479664545

78 €

WG.11.0706

5902479664552

EU-F-12b DEDICATED WIRED ROOM REGULATOR FOR EU-L-X WIFI CONTROLLER FOR 55MM FRAME SYSTEMS

- Functions:** room temperature control, additional control based on floor temperature (if floor sensor is used), RS485 wired communication **4-wire / no batteries**

- Equipment:** built-in room temperature sensor, humidity sensor, LCD display, no backlight, flush mountable in electrical box (ø60mm)

- * White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.11.0735

5902479665573

61 €

WG.11.0736

5902479665610

TEMPERATURE SENSORS - WIRED

EU-C-7p WIRED ROOM TEMPERATURE SENSOR

- Room temperature sensor

- * White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.03.0072

5902479661032

22 €

WG.03.0075

5902479662060

ROOM REGULATORS AND TEMPERATURE SENSORS - BATTERY, WIRELESS

EU-C-8r WIRELESS ROOM TEMPERATURE SENSOR

- Power: 2xAAA batteries

- * White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.03.0079

5902479661056

38 €

WG.03.0082

5902479662084

EU-C-8f WIRELESS FLOOR TEMPERATURE SENSOR

- Floor temperature sensor NTC type, power supply: 2x AAA batteries

- * White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.03.0076

5902479661643

43 €

WG.03.0078

5902479662220

WHILE STOCKS LAST

TECH CONTROLLERS

Spółka z ograniczoną odpowiedzialnością | ul. Biała Droga 31, 34-122 Wieprz | Tel. +48 33 330 00 07 | poczta@techsterowniki.pl



EU-C-mini WIRELESS ROOM TEMPERATURE SENSOR

Dimensions: 37mm x 37mm x 16mm

WHILE STOCKS LAST

WG.03.0085

5902479661636

37 €



EU-CL-mini WIRELESS ROOM TEMPERATURE SENSOR IN HERMETIC CASING

MEETS THE IP64 STANDARD

Dimensions: 44,3mm x 44,3mm x 17mm

WG.03.0084

5902479661636

43 €



EU-C-8zr WIRELESS OUTSIDE TEMPERATURE SENSOR

Power: 2xAAA batteries

WG.03.0083

5902479661063

39 €



EU-R-8b WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0188

5902479661070

49 €

WG.11.0192

5902479662091



EU-R-8x WIRELESS REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LCD display, 2xAA batteries, no backlit, mechanical buttons

WG.11.0734

5902479665924

48 €

WG.11.0760

5902479662091



EU-R-8b PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, temperature control on the basis of floor temperature (in case of using NTC floor sensor - not included), LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0195

5902479663647

66 €

WG.11.0196

5902479666099



EU-R-8s PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, 2xAAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0644

5902479664385

100 €

WG.11.0696

5902479664378



EU-R-8pb PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, powered 2xAAA batteries, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0699

5902479665009

108 €

WG.11.0700

5902479665016

WHILE STOCKS LAST

ROOM REGULATORS - 230V, WIRELESS



EU-R-8z WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LED display, power supply: 230V 50Hz to 5V included

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0202

5902479661087

66 €

WG.11.0203

5902479662107



EU-F-8z WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR FOR 55MM FRAME SYSTEMS

Functions: room temperature control, heating program with time limit, additional control based on floor temperature (in case of using NTC floor sensor - not included),

Equipment: built-in room temperature and humidity sensor, LCD display, no backlit, 230V powered, Flush mountable in electrical box (ø60mm), no backlit,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0634

5902479664408

89 €

WG.11.0686

5902479664415



EU-R-8pz PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, powered 230V, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0701

5902479665023

136 €

WG.11.0702

5902479665030



TECH
CONTROLLERS

ADDITIONAL MODULES AND ACTUATORS



EU-C-2N WINDOW SENSOR

Functions: wireless communication, window opening signal, heating control, compact in size, long-life battery, discreet design.
Power: EVE ER14250 S battery

| | | | |
|-----------------------|------------|---------------|------|
| RAL 9010- white | WG.03.0070 | 5902479661339 | 45 € |
| RAL 7016 - antracite | WG.03.0069 | 5902479664248 | |
| RAL 8017 - brown | WG.03.0071 | 5902479664255 | |
| RAL 8003 - golden oak | WG.03.0068 | 5902479664262 | |



EU-MW-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MW-1) or voltage relay (EU-MW-1-230V), operation in manual mode, wireless communication with main controller or temperature sensor (master/slave mode), in case of loss of communication, the contact is switched off 4 LEDs indicating: communication, power, manual mode, contact status

| | | | |
|--------------|------------|---------------|-------|
| EU-MW-1 | WG.05.0114 | 5902479661346 | 114 € |
| EU-MW-1-230V | WG.05.0116 | 5902479662374 | |



EU-MWN-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MWN-1) or voltage relay (EU-MWN-1-230V), wireless communication with main controller (slave mode), in case of loss of communication, the contact is switched off

| | | | |
|---------------|------------|---------------|-------|
| EU-MWN-1 | WG.05.0197 | 5902479664507 | 114 € |
| EU-MWN-1 230V | WG.05.0117 | 5902479664392 | |



EU-RP-4 SIGNAL REPEATER

The signal repeater is a small electronic device that increases the range of wireless communication between devices without the need for additional cables. Thanks to the device, controller which are away from main unit will be able to establish a stable connection

| | | | |
|--|------------|---------------|-------|
| | WG.05.0140 | 5902479662824 | 114 € |
|--|------------|---------------|-------|



EU-G-X WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S p, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 EU-L-X WiFi, EU-L-12, controller.
Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAA 1,5V batteries. new design, hidden registration button. **Available thread M28x1,5 adapter**

| | | | |
|--|------------|---------------|------|
| | WG.12.0045 | 5902479665054 | 97 € |
|--|------------|---------------|------|



STT-869 WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S p, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.
Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAA 1,5V batteries. new design, registration button built on the front of actuator. **Available thread M28x1,5 adapter**

| | | | |
|--|------------|---------------|------|
| | WG.12.0016 | 5902479662381 | 97 € |
|--|------------|---------------|------|



EU-i-1m MIXING VALVE CONTROLLER (1 MIXING VALVE ACTUATOR) (EXPANSION MODULE FOR MAIN CONTROLLER)

Functions: control of the three- or four-way mixing valve, return water temperature protection, weather-based regulation, week-based regulation, the possibility of connecting room regulator with RS or traditional communication.

| | | | |
|--|------------|---------------|-------|
| | WG.05.0030 | 5902479661612 | 139 € |
|--|------------|---------------|-------|



FLOOR TEMPERATURE SENSOR - NTC TYPE

(plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO

| | | | |
|-------|------------|---------------|------|
| 150cm | WG.01.0031 | 5902479661209 | 21 € |
| 250cm | WG.01.0032 | 5902479664279 | 22 € |



STT-230/2 THERMOELECTRIC ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28x1,5 screw thread, Stroke: 3,5 mm, Class: IP40. Opening time: under 5 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz

| | | | |
|-----------|------------|---------------|------|
| M30 x 1,5 | WG.01.0050 | 5902479660691 | 34 € |
| M28 x 1,5 | WG.01.0051 | 5902479661490 | |



STT-230/2 T THERMOELECTRIC ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28 x 1,5 screw thread, Class - IP45. Opening time: under 3,5 min. Stroke - 3,7mm, Max. operation temperature: 60°C. Power supply: 230V 50Hz

| | | | |
|-----------|------------|---------------|------|
| M30 x 1,5 | WG.01.0053 | 5902479663630 | 24 € |
| M28 x 1,5 | WG.01.0054 | 5902479665597 | 27 € |



STT-230/2 M THERMOELECTRIC ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 screw thread, Class - IP42. Opening time: under 4 min. to 3mm, Stroke - 5mm, Max. operation temperature: 60°C. Power supply: 230V 50Hz

| | | | |
|-----------|------------|---------------|------|
| M30 x 1,5 | WG.01.0052 | 5902479665108 | 24 € |
|-----------|------------|---------------|------|

Zone heating

Why it's worth it ?

When referring to zone heating, we mean an intelligent system for controlling heat in each room separately. Zone heating control is carried out using dedicated devices placed in individual rooms or zones for temperature measurement.


For each zone, the required temperature value is established for that particular location. The measurement devices communicate with the main controller or directly with the heating device. When the temperature is lower than the set value, they send a signal to start the heating device and open the underfloor or radiator valves in the respective zone. Conversely, when the set temperature is reached, the measurement devices send a signal to cease heating demand and close the radiator and underfloor valves in that zone. When all zones are heated to the set value, the heating device and pump receive a signal to end the need for further heating.

By opting for the installation of zone control systems, we do not have to rely on a single thermostat usually installed in the living room or hallway, which regulates the boiler's operation based on the temperature prevailing throughout the entire house.

Comfort in every room


By precisely determining the temperatures at which each room in our living space functions best, zone heating control allows for very accurate control of the heat source's operation. This enables us to avoid ad hoc heating of the house through temporary temperature changes, as well as cooling of the rooms, for example, by frequently opening windows, which, as we know, affects the boiler's operation. Indicating optimal temperatures and, above all, stabilizing them at a certain level allows for a significant reduction in energy consumption, which in turn directly translates into the contents of our wallets.

Air recuperation and zone heating



- The supply air temperature does not allow for heating the rooms, hence heating will be required.
- Recuperation serves for mechanical air exchange with heat recovery, and in this aspect, it works perfectly.
- Zone heating will allow for reducing the supply of necessary energy in individual rooms.

The frequency of operation of the heating device




- Operation of the heating device
- Outdoor temperature

The total time for which the signal is provided to the device is shorter in the case of controlling the heating curve without a signal; such a source would have to operate 24 hours.

The number of activation signals does not equal the number of starts of the heat source - this is decided by the source's automation.


- Customizable room temperature comfort as desired by the user
- No underheated rooms
- No overheated rooms
- Elimination of existing installation imperfections
- No user interference with the heat source
- Prolongation of the heating device's lifespan by reducing its operating time
- Possibility of remote temperature management
- Window opening control
- Wireless communication - possibility of installation in an existing building
- Reduction of energy consumption

Variability of heating needs depending on the location of the rooms



- Room on the north side
- Room on the south side
- Outdoor temperature

Much more frequent radiator opening in the room on the north side of the building. The northern side of the building lacks passive heat gains from the sun on sunny days. Zone heating eliminates unnecessary heating activation when the room is already heated.




Opening windows and energy losses

Opening a window causes the heating to turn off. This prevents unnecessary energy losses during ventilation.



WIRED FLOOR HEATING SYSTEM - 5 SERIES



EU-L-5s WIRED CONTROLLER FOR THERMOSTATIC ACTUATORS (8 SECTIONS)

Functions: Possibility of control up to 50 thermostatic actuators via 8 room regulators:
 - 3 zones have 4 outputs each (in case of greater amount of actuators max load is 0,3 A),
 - 5 zones have 2 outputs each (in case of greater amount of actuators max load is 0,3 A),

WG.20.0134

5902479663784

105 €

ROOM REGULATORS AND TEMPERATURE SENSORS - BATTERY, WIRED



EU-294 v1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, heating/cooling program with time limit, wired communication

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0144

5902479661018

42 €

WG.11.0147

5902479662053



EU-T-2.1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, humidity sensor, heating/cooling program with time limit, wired communication

Equipment: built-in room temperature sensor, LCD display, 2xAA Batteries,

WG.11.0642

5902479665085

65 €



EU-295 v3 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlit,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries

WG.11.0151

5902479661544

57 €



EU-297 v3 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlit,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0155

5902479662947

91 €

WG.11.0156

5902479662954



EU-297z v3 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlit, possibility of powering regulator from EU-L-5s controller

Equipment: built-in room temperature sensor, LCD display, 230V powered, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0158

5902479663746

100 €

WG.11.0604

5902479663753



EU-T-3.1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlit,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0160

5902479663906

88 €

WG.11.0601

5902479664217



EU-T-4.1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlit, Optimum Start function, heating/cooling function, wired communication

Equipment: built-in room temperature sensor, LCD display, 2xAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0693

5902479664590

65 €



EU-T-5z WiFi WIRED TWO-STATE ROOM REGULATOR WITH WIFI

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor EU-C-8f is used), temporary display backlit,

Equipment: wireless temperature sensor EU-C-mini included, LCD display, 230V powered, built-in WiFi module, Flush mountable in electrical box (ø60mm)

Maintain of the system via web app: www.emodul.eu

WG.20.0168

5902479665665

149 €



EU-292 v3 WIRED TWO-STATE ROOM REGULATOR (3MM GLASS)

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlit, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wired communication

Equipment: built-in room temperature sensor, front panel made of 3mm glass

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0137

5902479660257

82 €

WG.11.0139

5902479660264



EU-293 v3 WIRED TWO-STATE ROOM REGULATOR (1MM GLASS)

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlight, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wired communication,

Equipment: built-in room temperature sensor, front panel made of 1mm glass, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WHILE STOCKS LAST

WG.11.0142
WG.11.0143

5902479662886
5902479662893

104 €



EU-293z v3 WIRED TWO-STATE ROOM REGULATOR (1MM GLASS)

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlight, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wired communication, possibility of powering regulator from EU-L-5s controller

Equipment: built-in room temperature sensor, LCD display, 230V powered, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WHILE STOCKS LAST

WG.11.0645
WG.11.0697

5902479663791
5902479663807

124 €



EU-F-2z v1 WIRED ROOM REGULATOR FOR 55MM FRAME SYSTEMS

Functions: control of the room temperature, heating/cooling, display autolock function,

Equipment: built-in room temperature sensor, LCD display with no backlight, power supply: 230V,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0609
WG.11.0636

5902479664095
5902479664132

75 €



EU-F-4z v1 WIRED ROOM REGULATOR FOR 55MM FRAME SYSTEMS

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlight, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wired communication

Equipment: built-in room temperature sensor, front panel made of 3mm glass, 230V powered,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0633
WG.11.0687

5902479664118
5902479664156

104 €

ACCESORIES AND ACTUATORS



FLOOR TEMPERATURE SENSOR - NTC TYPE

(plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO

150cm
250cm

WG.01.0031
WG.01.0031

5902479661209
5902479664279

21 €
22 €



STT-230/2 THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28x1,5 screw thread, Stroke: 3,5 mm, Class: IP40. Opening time: under 5 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5
M28 x 1,5

WG.01.0050
WG.01.0051

5902479660691
5902479661490

34 €



STT-230/2 T THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28 x 1,5 screw thread, Class - IP45. Opening time: under 3,5 min. Stroke - 3,7mm, Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5
M28 x 1,5

WG.01.0053
WG.01.0054

5902479663630
5902479665597

24 €
27 €



STT-230/2 M THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 screw thread, Class - IP42.. Opening time: under 4 min. to 3mm, Stroke - 5mm, Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5

WG.01.0052

5902479665108

24 €



TECH
CONTROLLERS

WIRELESS FLOOR HEATING SYSTEM WITH INTERNET - 8 SERIES

Possibility of wireless control over thermostatic actuators

EU- L-8e WIRELESS CONTROLLER FOR THERMOSTATIC ACTUATORS (8 SECTIONS)

- Functions:** Possibility of controlling up to 50 thermostatic actuators via 8 system room temperature sensors or room regulators
- 3 zones have 4 outputs each (in case of greater amount of actuators max load is 0,3 A),
 - 5 zones have 2 outputs each (in case of greater amount of actuators max load is 0,3 A),
 - one 230V output for pump
 - voltage-free contact (e.g. for controlling the heating device)
 - possibility of connecting EU-M8e control panel with RS communication
 - possibility of connecting EU-S05 Ethernet or EU-WiFi RS for controlling the installation via Internet
 - **possibility of connecting EU-i-1m mixing valve module or EU-I-1 mixing valve controller**
 - software update via USB
 - cooling and heating function
 - possibility of connecting 3 additional KTY sensors or outdoor sensor (1 input replace 1 sensor or 1 room regulator)



WG.20.0050

5902479662640

306 €

ROOM REGULATORS AND TEMPERATURE SENSORS - BATTERY, WIRELESS

EU-C-8r WIRELESS ROOM TEMPERATURE SENSOR

Power: 2xAAA batteries

* White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.03.0079

5902479661056

38 €

WG.03.0082

5902479662084

EU-C-8f WIRELESS FLOOR TEMPERATURE SENSOR

Floor temperature sensor NTC type, power supply: 2x AAA batteries

* White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.03.0076

5902479661643

43 €

WG.03.0078

5902479662220

WHILE STOCKS LAST

EU-C-mini WIRELESS ROOM TEMPERATURE SENSOR

Dimensions: 37mm x 37mm x 16mm



WG.03.0085

5902479661636

37 €

WHILE STOCKS LAST

EU-CL-mini WIRELESS ROOM TEMPERATURE SENSOR IN HERMETIC CASING

MEETS THE IP64 STANDARD

Dimensions: 44,3mm x 44,3mm x 17mm



WG.03.0084

5902479661636

43 €

EU-C-8zr WIRELESS OUTSIDE TEMPERATURE SENSOR

Power: 2xAAA batteries



WG.03.0083

5902479661063

39 €

EU-R-8b WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.11.0188

5902479661070

49 €

WG.11.0192

5902479662091

EU-R-8x WIRELESS REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LCD display, 2xAA batteries, no backlit, mechanical buttons



WG.11.0734

5902479665924

48 €

WG.11.0760

5902479666099

EU-R-8b PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, temperature control on the basis of floor temperature (in case of using NTC floor sensor - not included), LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.11.0195

5902479663647

66 €

WG.11.0196

5902479663654

EU-R-8s PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, 2xAAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.11.0644

5902479664385

100 €

WG.11.0696

5902479664378



EU-R-8pb PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, powered 2xAAA batteries, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WHILE STOCKS LAST

WG.11.0699
WG.11.0700

5902479665009
5902479665016

108 €

ROOM REGULATORS - 230V, WIRELESS



EU-R-8z WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LED display, power supply: 230V 50Hz to 5V included

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0202
WG.11.0203

5902479661087
5902479662107

66 €



EU-F-8z WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR FOR 55MM FRAME SYSTEMS

Functions: room temperature control, heating program with time limit, additional control based on floor temperature (in case of using NTC floor sensor - not included),

Equipment: built-in room temperature and humidity sensor, LCD display, no backlit, 230V powered, Flush mountable in electrical box (ø60mm), no backlit,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0634
WG.11.0686

5902479664408
5902479664415

89 €



EU-R-8pb PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, powered 230V, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0701
WG.11.0702

5902479665023
5902479665030

136 €

ADDITIONAL MODULES AND ACTUATORS



EU-M-8n WIRELESS CONTROL PANEL FOR EU-L-8e CONTROLLER (FLUSH-MOUNTABLE)

Principle of operation: Controller is designed to control and preview the parameters of floor heating system.

Functions: Changing the parameters for each zone (schedule settings, set temperature), possibility of enabling/disabling particular zone, time/date settings, brightness settings, screensaver, alarm clock, screen lock, easy installation in an electrical box (ø60mm). Power supply: 230V 50Hz.

ONLY FOR EU-L-8e controller!

WHILE STOCKS LAST

WG.11.0168
WG.20.0139

5902479663883
5902479664453

295 €



EU-C-2N WINDOW SENSOR

Functions: wireless communication, window opening signal, heating control, compact in size, long-life battery, discreet design.

Power: EVE ER14250 S battery

RAL 9010 - white
RAL 7016 - antracite
RAL 8017 - brown
RAL 8003 - golden oak

WG.03.0070
WG.03.0069
WG.03.0071
WG.03.0068

5902479661339
5902479664248
5902479664255
5902479664262

45 €



FLOOR TEMPERATURE SENSOR - NTC TYPE

(plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO

150cm
250cm

WG.01.0031
WG.01.0031

5902479661209
5902479664279

21 €
22 €



EU-WiFi RS WIFI INTERNET MODULE (WIFI CONNECTION)

Functions: Same as in EU-505. Internet connection via WiFi signal

WG.05.0040

5902479660974

237 €



EU-505 INTERNET MODULE

Functions: remote control of the floor heating system, control of the set temperature in each zone, possibility of define the schedules, preview the temperatures history for each zone, possibility of personalization the main screen, alarms notifications via e-mail.

Equipment: power supply: 5V DC, T-connector for RS, RS communication cable for main controller.

WG.05.0025

5902479660578

221 €



EU-i-1m MIXING VALVE CONTROLLER (1 MIXING VALVE ACTUATOR) (EXPANSION MODULE FOR MAIN CONTROLLER)

Fuctions: control of the three- or four-way mixing valve, return water temperature protection, weather-based regulation, week-based regulation, the possibility of connecting room regulator with RS or traditional communication.

WG.05.0030

5902479661612

139 €



TECH
CONTROLLERS



EU-MW-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MW-1) or voltage relay (EU-MW-1-230V), operation in manual mode, wireless communication with main controller or temperature sensor (master/slave mode), in case of loss of communication, the contact is switched off 4 LEDs indicating: communication, power, manual mode, contact status

EU-MW-1
EU-MW-1-230V

WG.05.0114
WG.05.0116

5902479661346
5902479662374

114 €



EU-MWN-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MWN-1) or voltage relay (EU-MWN-1-230V), wireless communication with main controller (slave mode), in case of loss of communication, the contact is switched off

EU-MWN-1
EU-MWN-1 230V

WG.05.0197
WG.05.0117

5902479664507
5902479664392

114 €



EU-RP-4 SIGNAL REPEATER

The signal repeater is a small electronic device that increases the range of wireless communication between devices without the need for additional cables. Thanks to the device, controller which are away from main unit will be able to establish a stable connection

WG.05.0140

5902479662824

114 €



EU-513 INPUTS INTEGRATOR - 5

Functions: Integration of 5 voltage inputs, control of one 230V output

WG.05.0027

5902479661414

67 €



EU-G-X WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S p, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 EU-L-X WiFi, EU-L-12, controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAA 1,5V batteries. new design, hidden registration button. **Available thread M28x1,5 adapter**

WG.12.0045

5902479665054

97 €



STT-869 WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S p, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAA 1,5V batteries. new design, registration button built on the front of actuator. **Available thread M28x1,5 adapter**

WG.12.0016

5902479662381

97 €



STT-230/2 THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28x1,5 screw thread, Stroke: 3,5 mm, Class: IP40. Opening time: under 5 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5
M28 x 1,5

WG.01.0050
WG.01.0051

5902479660691
5902479661490

34 €



STT-230/2 T THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28 x 1,5 screw thread, Class - IP45. Opening time: under 3,5 min. Stroke - 3,7mm, Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5
M28 x 1,5

WG.01.0053
WG.01.0054

5902479663630
5902479665597

24 €

27 €



STT-230/2 M THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 screw thread, Class - IP42.. Opening time: under 4 min. to 3mm, Stroke - 5mm, Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5

WG.01.0052

5902479665108

24 €



**WIRELESS
ROOM REGULATOR
FOR 55mm
FRAME SYSTEMS
EU-F-8z**

EU-L-9r WIRED/WIRELESS CONTROLLER FOR THERMOSTATIC ACTUATORS (8 SECTIONS)

- Functions:**
- possibility of control up to **50** thermostatic actuators by **19** outputs:
 - 3 zones have 3 outputs each (in case of greater amount of actuators max load is 0,3 A),
 - 5 zones have 2 outputs each (in case of greater amount of actuators max load is 0,3 A),
 - one 230V output for pump
 - voltage-free contact (e.g. for controlling the heating device)
 - possibility of connecting EU-i-1m mixing valve module or EU-i-1 mixing valve controller
 - possibility of connecting up to **4 controllers in series (up to 32 zones)** and managing system via 1 control panel
 - possibility of controlling the system via Internet (eModul app)
 - **heating/cooling mode**
 - 4-wire cord for communication with peripheral devices
 - possibility of connecting system wireless room temperature sensors, room regulators or electric actuators
 - **software update via USB**

WHILE STOCKS LAST

WG.20.0056

5902479662831

382 €

ROOM REGULATORS AND SENSORS POWERED FROM MAIN CONTROLLER - DEDICATED

EU-R-9b DEDICATED WIRED ROOM REGULATOR FOR EU-L-9r CONTROLLER

Functions: room temperature control, additional control based on floor temperature (if floor sensor is used), wired communication **4-wire / no batteries**

Equipment: built-in room temperature sensor, LCD display, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WHILE STOCKS LAST

WG.11.0205

5902479662275

46 €

WG.11.0208

5902479662329

EU-R-9s PLUS DEDICATED WIRED ROOM REGULATOR FOR EU-L-9r CONTROLLER

Functions: room temperature control, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlit, communication **4-wire / no batteries**

Equipment: built-in room temperature and humidity sensor, LCD display,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WHILE STOCKS LAST

WG.11.0211

5902479663852

74 €

WG.11.0107

5902479664170

TEMPERATURE SENSORS - WIRED

EU-C-7p WIRED ROOM TEMPERATURE SENSOR

Room temperature sensor

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.03.0072

5902479661032

22 €

WG.03.0075

5902479662060

ROOM REGULATORS AND TEMPERATURE SENSORS - BATTERY, WIRELESS

EU-C-8r WIRELESS ROOM TEMPERATURE SENSOR

Power: 2xAAA batteries

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.03.0079

5902479661056

38 €

WG.03.0082

5902479662084

EU-C-8f WIRELESS FLOOR TEMPERATURE SENSOR

Floor temperature sensor NTC type, power supply: 2x AAA batteries

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.03.0076

5902479661643

43 €

WG.03.0078

5902479662220

EU-C-mini WIRELESS ROOM TEMPERATURE SENSOR

Dimensions: 37mm x 37mm x 16mm

WHILE STOCKS LAST

WG.03.0085

5902479661636

37 €

EU-CL-mini WIRELESS ROOM TEMPERATURE SENSOR IN HERMETIC CASING

MEETS THE IP64 STANDARD

Dimensions: 44,3mm x 44,3mm x 17mm

WG.03.0084

5902479661636

43 €

EU-C-8zr WIRELESS OUTSIDE TEMPERATURE SENSOR

Power: 2xAAA batteries

WG.03.0083

5902479661063

39 €

EU-R-8b WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0188

5902479661070

49 €

WG.11.0192

5902479662091



TECH
CONTROLLERS



EU-R-8x WIRELESS REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LCD display, 2xAAA batteries, no backlit, mechanical buttons

WG.11.0734
WG.11.0760

5902479665924
5902479666099

48 €



EU-R-8b PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, temperature control on the basis of floor temperature (in case of using NTC floor sensor - not included), LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0195
WG.11.0196

5902479663647
5902479663654

66 €



EU-R-8s PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, 2xAAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0644
WG.11.0696

5902479664385
5902479664378

100 €



EU-R-8pb PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, powered 2xAAA batteries, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0699
WG.11.0700

5902479665009
5902479665016

108 €

WHILE STOCKS LAST

ROOM REGULATORS - 230V, WIRELESS



EU-R-8z WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LED display, power supply: 230V 50Hz to 5V included

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0202
WG.11.0203

5902479661087
5902479662107

66 €



EU-F-8z WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR FOR 55MM FRAME SYSTEMS

Functions: room temperature control, heating program with time limit, additional control based on floor temperature (in case of using NTC floor sensor - not included).

Equipment: built-in room temperature and humidity sensor, LCD display, no backlit, 230V powered, Flush mountable in electrical box (ø60mm), no backlit,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0634
WG.11.0686

5902479664408
5902479664415

89 €



EU-R-8pz PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, powered 230V, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0701
WG.11.0702

5902479665023
5902479665030

136 €

ADDITIONAL MODULES AND ACTUATORS



EU-M-9r WIRED CONTROL PANEL + WIFI MODULE (FLUSH MOUNTABLE)

Functions: Zone registration, changing parameters for each zone (schedules, set temperature), possibility of activate/deactivate zone, date/hour settings for whole system, screensaver, screen lock. **NO TEMPERATURE SENSOR BUILT IN CONTROLLER., WiFi communication (system management via eModul app),** Flush mountable in electrical box (ø60mm). Power supply 230V 50Hz, wired communication 4-cable cord / no batteries

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0175
WG.11.0178

5902479662428
5902479662855

451 €

WHILE STOCKS LAST



EU-M-9t WIRED CONTROL PANEL + WIFI MODULE

Functions: Zone registration, changing parameters for each zone (schedules, set temperature), possibility of activate/deactivate zone, date/hour settings for whole system, screensaver, screen lock. **NO TEMPERATURE SENSOR BUILT IN CONTROLLER., WiFi communication (system management via eModul app),** wired communication 4-cable cord / no batteries, RS power adapter in set,

WG.11.0252
WG.11.0586

5902479664019
5902479664439

451 €

WHILE STOCKS LAST



EU-C-2N WINDOW SENSOR

Functions: wireless communication, window opening signal, heating control, compact in size, long-life battery, discreet design.

Power: EVE ER14250 S battery

| | | | |
|-----------------------|------------|---------------|------|
| RAL 9010- white | WG.03.0070 | 5902479661339 | 45 € |
| RAL 7016 - antracite | WG.03.0069 | 5902479664248 | |
| RAL 8017 - brown | WG.03.0071 | 5902479664255 | |
| RAL 8003 - golden oak | WG.03.0068 | 5902479664262 | |



EU-MW-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MW-1) or voltage relay (EU-MW-1-230V), operation in manual mode, wireless communication with main controller or temperature sensor (master/slave mode), in case of loss of communication, the contact is switched off 4 LEDs indicating: communication, power, manual mode, contact status

| | | | |
|--------------|------------|---------------|-------|
| EU-MW-1 | WG.05.0114 | 5902479661346 | 114 € |
| EU-MW-1-230V | WG.05.0116 | 5902479662374 | |



EU-MWN-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MWN-1) or voltage relay (EU-MWN-1-230V), wireless communication with main controller (slave mode), in case of loss of communication, the contact is switched off

| | | | |
|---------------|------------|---------------|-------|
| EU-MWN-1 | WG.05.0197 | 5902479664507 | 114 € |
| EU-MWN-1 230V | WG.05.0117 | 5902479664392 | |



EU-RP-4 SIGNAL REPEATER

The signal repeater is a small electronic device that increases the range of wireless communication between devices without the need for additional cables. Thanks to the device, controller which are away from main unit will be able to establish a stable connection

| | | | |
|--|------------|---------------|-------|
| | WG.05.0140 | 5902479662824 | 114 € |
|--|------------|---------------|-------|



EU-G-X WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S p, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 EU-L-X WiFi, EU-L-12, controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAA 1,5V batteries. new design, hidden registration button. **Available thread M28x1,5 adapter**

| | | | |
|--|------------|---------------|------|
| | WG.12.0045 | 5902479665054 | 97 € |
|--|------------|---------------|------|



STT-869 WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S p, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAA 1,5V batteries. new design, registration button built on the front of actuator, **Available thread M28x1,5 adapter**

| | | | |
|--|------------|---------------|------|
| | WG.12.0016 | 5902479662381 | 97 € |
|--|------------|---------------|------|



EU-i-1m MIXING VALVE CONTROLLER (1 MIXING VALVE ACTUATOR) (EXPANSION MODULE FOR MAIN CONTROLLER)

Fuctions: control of the three- or four-way mixing valve, return water temperature protection, weather-based regulation, week-based regulation, the possibility of connecting room regulator with RS or traditional communication.

| | | | |
|--|------------|---------------|-------|
| | WG.05.0030 | 5902479661612 | 139 € |
|--|------------|---------------|-------|



FLOOR TEMPERATURE SENSOR - NTC TYPE

(plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO

| | | | |
|-------|------------|---------------|------|
| 150cm | WG.01.0031 | 5902479661209 | 21 € |
| 250cm | WG.01.0031 | 5902479664279 | 22 € |



EU-291P NTC WIRED OUTSIDE TEMPERATURE SENSOR

Sensor dedicated for EU-L-9 controller

| | | | |
|--|------------|---------------|------|
| | WG.03.0064 | 5902479662732 | 21 € |
|--|------------|---------------|------|



STT-230/2 THERMOELECTRIC ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28x1,5 screw thread, Stroke: 3,5 mm, Class: IP40. Opening time: under 5 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz

| | | | |
|-----------|------------|---------------|------|
| M30 x 1,5 | WG.01.0050 | 5902479660691 | 34 € |
| M28 x 1,5 | WG.01.0051 | 5902479661490 | |



STT-230/2 T THERMOELECTRIC ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28 x 1,5 screw thread, Class - IP45. Opening time: under 3,5 min. Stroke - 3,7mm, Max. operation temperature: 60°C. Power supply: 230V 50Hz

| | | | |
|-----------|------------|---------------|------|
| M30 x 1,5 | WG.01.0053 | 5902479663630 | 24 € |
| M28 x 1,5 | WG.01.0054 | 5902479665597 | 27 € |



STT-230/2 M THERMOELECTRIC ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 screw thread, Class - IP42.. Opening time: under 4 min. to 3mm, Stroke - 5mm, Max. operation temperature: 60°C. Power supply: 230V 50Hz

| | | | |
|-----------|------------|---------------|------|
| M30 x 1,5 | WG.01.0052 | 5902479665108 | 24 € |
|-----------|------------|---------------|------|



WIRED FLOOR HEATING SYSTEM - 10 SERIES



EU-L-10 WIRED CONTROLLER FOR THERMOSTATIC ACTUATORS (10 SECTIONS)

Functions: • possibility of control up to 50 thermostatic actuators by 18 outputs:

- 8 zones have 2 outputs each (in case of greater amount of actuators max load is 0,3 A),
- 2 zones have 1 output each (in case of greater amount of actuators max load is 0,3 A),
- one 230V output for pump
- voltage-free contact (e.g. for controlling the heating device)
- voltage contact for controlling floor pump
- 2 minutes delay for switching on voltage-free contact and pump contact

WG.20.004

5902479662497

178 €

ROOM REGULATORS AND SENSORS POWERED FROM MAIN CONTROLLER - DEDICATED



EU-R-10b DEDICATED WIRED ROOM REGULATOR FOR EU-L-10 CONTROLLER

Functions: room temperature control, wired communication 3-wire / no batteries

Equipment: built-in room temperature sensor, LCD display, no backlight

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0180

5902479662503

47 €

WG.11.0181

5902479662343



EU-R-10s PLUS DEDICATED WIRED ROOM REGULATOR FOR EU-L-10 CONTROLLER

Functions: room temperature control, day/night program, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlight, 3-wire / no batteries

Equipment: built-in room temperature sensor, LCD display,

WG.11.0184

5902479663876

74 €

WG.11.0185

5902479664187

ROOM REGULATORS AND TEMPERATURE SENSORS - BATTERY, WIRED



EU-294 v1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, heating/cooling program with time limit, wired communication

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries, no backlight

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0144

5902479661018

42 €

WG.11.0147

5902479662053



EU-T-2.1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, humidity sensor, heating/cooling program with time limit, wired communication

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries,

WG.11.0642

5902479665085

65 €



EU-295 v3 TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlight,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries

WG.11.0151

5902479661544

57 €



EU-297 v3 TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlight,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0155

5902479662947

91 €

WG.11.0156

5902479662954



EU-297z v3 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlight, possibility of powering regulator from EU-L-5s controller

Equipment: built-in room temperature sensor, LCD display, 230V powered, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0158

5902479663746

100 €

WG.11.0604

5902479663753



EU-T-3.1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlight,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0160

5902479663906

88 €

WG.11.0601

5902479664217



EU-T-4.1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlight, Optimum Start function, heating/cooling function, wired communication

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0693

5902479664590

65 €



EU-T-5z WiFi WIRED TWO-STATE ROOM REGULATOR WITH WIFI

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor EU-C-8f is used), temporary display backlit.

Equipment: wireless temperature sensor EU-C-mini included, LCD display, 230V powered, built-in WiFi module, Flush mountable in electrical box (ø60mm)

Maintain of the system via web app: www.emodul.eu

WG.20.0168

5902479665665

149 €



EU-292 v3 WIRED TWO-STATE ROOM REGULATOR (3MM GLASS)

Functions: room temperature control, weekly heating program, heating/cooling function, manual mode, day/night program, temporary display backlit, additional control based on floor temperature (if floor sensor is used), Optimum Start function, wired communication

Equipment: built-in room temperature sensor, front panel made of 3mm glass

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0137

5902479660257

82 €

WG.11.0139

5902479660264



EU-293 v3 WIRED TWO-STATE ROOM REGULATOR (1MM GLASS)

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlit, temperature control on the basis of floor temperature (in case of using floor sensor), Optimum Start function, heating/cooling function, wired communication, Flush mountable in electrical box (ø60mm)

Equipment: built-in room temperature sensor, front panel made of 1mm glass

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0142

5902479662886

104 €

WG.11.0143

5902479662893



EU-293z v3 WIRED TWO-STATE ROOM REGULATOR (1MM GLASS)

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlit, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wired communication, possibility of powering regulator from EU-L-5s controller

Equipment: built-in room temperature sensor, LCD display, 230V powered, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0645

5902479663791

124 €

WG.11.0697

5902479663807



EU-F-2z v1 WIRED ROOM REGULATOR FOR 55MM FRAME SYSTEMS

Functions: control of the room temperature, heating/cooling, display autolock function,

Equipment: built-in room temperature sensor, LCD display with no backlit, power supply: 230V,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0609

5902479664095

75 €

WG.11.0636

5902479664132



EU-F-4z v1 WIRED ROOM REGULATOR FOR 55MM FRAME SYSTEMS

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlit, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wired communication

Equipment: built-in room temperature sensor, front panel made of 3mm glass, 230V powered,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0633

5902479664118

104 €

WG.11.0687

5902479664156

ACCESORIES AND ACTUATORS



FLOOR TEMPERATURE SENSOR - NTC TYPE

(plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO

150cm

WG.01.0031

5902479661209

21 €

250cm

WG.01.0031

5902479664279

22 €



STT-230/2 THERMOELECTRIC ACTUATOR

ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28x1,5 screw thread, Stroke: 3,5 mm, Class: IP40. Opening time: under 5 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5

WG.01.0050

5902479660691

34 €

M28 x 1,5

WG.01.0051

5902479661490



STT-230/2 T THERMOELECTRIC ACTUATOR

ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28 x 1,5 screw thread, Class - IP45. Opening time: under 3,5 min. Stroke - 3,7mm, Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5

WG.01.0053

5902479663630

24 €

M28 x 1,5

WG.01.0054

5902479665597

27 €



STT-230/2 M THERMOELECTRIC ACTUATOR

ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 screw thread, Class - IP42. Opening time: under 4 min. to 3mm, Stroke - 5mm, Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5

WG.01.0052

5902479665108

24 €



TECH
CONTROLLERS

EU-L-X WIFI WIRED/WIRELESS CONTROLLER FOR THERMOSTATIC ACTUATORS (8 SECTIONS) WITH WIFI

- Functions:**
- possibility of control up to **50** thermostatic actuators by **19** outputs:
 - 3 zones have 3 outputs each (in case of greater amount of actuators max load is 0,3 A),
 - 5 zones have 2 outputs each (in case of greater amount of actuators max load is 0,3 A),
 - one 230V output for pump
 - voltage-free contact (e.g. for controlling the heating device)
 - possibility of connecting EU-i-1m mixing valve module or EU-i-1 mixing valve controller
 - possibility of controlling the system via Internet (eModul app)
 - **heating/cooling mode**
 - RS-485 4-wire cord for communication with peripheral devices
 - possibility of connecting system wireless room temperature sensors, room regulators or electric actuators
 - **software update via USB**



WG.20.0158

5902479664330

402 €

ROOM REGULATORS AND SENSORS POWERED FROM MAIN CONTROLLER - DEDICATED RS 485

EU-R-X DEDICATED WIRED ROOM REGULATOR FOR EU-L-X WIFI CONTROLLER

- Functions:** room temperature control, additional control based on floor temperature (if floor sensor is used), RS485 wired communication **4-wire / no batteries**
- Equipment:** built-in room temperature sensor, LCD display, no backlight



WG.11.0737

5902479665627

48 €

EU-R-12b DEDICATED WIRED ROOM REGULATOR FOR EU-L-X WIFI CONTROLLER

- Functions:** room temperature control, additional control based on floor temperature (if floor sensor is used), RS485 wired communication **4-wire / no batteries**
- Equipment:** built-in room temperature sensor, humidity sensor, LCD display, no backlight
- * White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.11.0703

5902479664569

65 €

WG.11.0704

5902479664576

EU-R-12s DEDICATED WIRED ROOM REGULATOR FOR EU-L-X WIFI CONTROLLER

- Functions:** room temperature control, additional control based on floor temperature (if floor sensor is used), RS485 wired communication **4-wire / no batteries**
- Equipment:** built-in room temperature sensor, humidity sensor, LCD display with temporary backlight
- * White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.11.0705

5902479664545

78 €

WG.11.0706

5902479664552

EU-F-12b DEDICATED WIRED ROOM REGULATOR FOR EU-L-X WIFI CONTROLLER FOR 55MM FRAME SYSTEMS

- Functions:** room temperature control, additional control based on floor temperature (if floor sensor is used), RS485 wired communication **4-wire / no batteries**
- Equipment:** built-in room temperature sensor, humidity sensor, LCD display, no backlight, flush mountable in electrical box (ø60mm)
- * White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.11.0735

5902479665573

61 €

WG.11.0736

5902479665610

TEMPERATURE SENSORS - WIRED

EU-C-7p WIRED ROOM TEMPERATURE SENSOR

- Room temperature sensor
- * White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.03.0072

5902479661032

22 €

WG.03.0075

5902479662060

ROOM REGULATORS AND TEMPERATURE SENSORS - BATTERY, WIRELESS

EU-C-8r WIRELESS ROOM TEMPERATURE SENSOR

- Power: 2xAAA batteries
- * White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.03.0079

5902479661056

38 €

WG.03.0082

5902479662084

EU-C-8f WIRELESS FLOOR TEMPERATURE SENSOR

- Floor temperature sensor NTC type, power supply: 2x AAA batteries
- * White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.03.0076

5902479661643

43 €

WG.03.0078

5902479662220

WHILE STOCKS LAST

EU-C-mini WIRELESS ROOM TEMPERATURE SENSOR

Dimensions: 37mm x 37mm x 16mm



WG.03.0085

5902479661636

37 €

WHILE STOCKS LAST

EU-CL-mini WIRELESS ROOM TEMPERATURE SENSOR IN HERMETIC CASING

MEETS THE IP64 STANDARD

Dimensions: 44,3mm x 44,3mm x 17mm



WG.03.0084

5902479661636

43 €



EU-C-8zr WIRELESS OUTSIDE TEMPERATURE SENSOR

Power: 2xAAA batteries

WG.03.0083

5902479661063

39 €



EU-R-8b WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0188

5902479661070

49 €

WG.11.0192

5902479662091



EU-R-8x WIRELESS REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LCD display, 2xAA batteries, no backlit, mechanical buttons

WG.11.0734

5902479665924

48 €



EU-R-8b PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, temperature control on the basis of floor temperature (in case of using NTC floor sensor - not included), LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0195

5902479663647

66 €

WG.11.0196

5902479663654



EU-R-8s PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, 2xAAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0644

5902479664385

100 €

WG.11.0696

5902479664378



EU-R-8pb PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, powered 2xAAA batteries, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0699

5902479665009

108 €

WG.11.0700

5902479665016

WHILE STOCKS LAST

ROOM REGULATORS - 230V, WIRELESS



EU-R-8z WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LED display, power supply: 230V 50Hz to 5V included

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0202

5902479661087

66 €

WG.11.0203

5902479662107



EU-F-8z WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR FOR 55MM FRAME SYSTEMS

Functions: room temperature control, heating program with time limit, additional control based on floor temperature (in case of using NTC floor sensor - not included),

Equipment: built-in room temperature and humidity sensor, LCD display, no backlit, 230V powered, Flush mountable in electrical box (ø60mm), no backlit,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0634

5902479664408

89 €

WG.11.0686

5902479664415



EU-R-8pz PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, powered 230V, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0701

5902479665023

136 €

WG.11.0702

5902479665030

ADDITIONAL MODULES AND ACTUATORS



EU-C-2N WINDOW SENSOR

Functions: wireless communication, window opening signal, heating control, compact in size, long-life battery, discreet design.

Power: EVE ER14250 S battery

RAL 9010 - white

WG.03.0070

5902479661339

RAL 7016 - antracite

WG.03.0069

5902479664248

RAL 8017 - brown

WG.03.0071

5902479664255

RAL 8003 - golden oak

WG.03.0068

5902479664262

45 €



TECH
CONTROLLERS



EU-MW-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MW-1) or voltage relay (EU-MW-1-230V), operation in manual mode, wireless communication with main controller or temperature sensor (master/slave mode), in case of loss of communication, the contact is switched off 4 LEDs indicating: communication, power, manual mode, contact status

EU-MW-1
EU-MW-1-230V

WG.05.0114
WG.05.0116

5902479661346
5902479662374

114 €



EU-MWN-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MWN-1) or voltage relay (EU-MWN-1-230V), wireless communication with main controller (slave mode), in case of loss of communication, the contact is switched off

EU-MWN-1
EU-MWN-1-230V

WG.05.0197
WG.05.0117

5902479664507
5902479664392

114 €



EU-RP-4 SIGNAL REPEATER

The signal repeater is a small electronic device that increases the range of wireless communication between devices without the need for additional cables. Thanks to the device, controller which are away from main unit will be able to establish a stable connection

WG.05.0140

5902479662824

114 €



EU-G-X WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S p, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 EU-L-X WiFi, EU-L-12, controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAAA 1,5V batteries. new design, hidden registration button. **Available thread M28x1,5 adapter**

WG.12.0045

5902479665054

97 €



STT-869 WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S p, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAAA 1,5V batteries. new design, registration button built on the front of actuator, **Available thread M28x1,5 adapter**

WG.12.0016

5902479662381

97 €



EU-i-1m MIXING VALVE CONTROLLER (1 MIXING VALVE ACTUATOR) (EXPANSION MODULE FOR MAIN CONTROLLER)

Fuctions: control of the three- or four-way mixing valve, return water temperature protection, weather-based regulation, week-based regulation, the possibility of connecting room regulator with RS or traditional communication.

WG.05.0030

5902479661612

139 €



FLOOR TEMPERATURE SENSOR - NTC TYPE

(plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO

150cm
250cm

WG.01.0031
WG.01.0031

5902479661209
5902479664279

21 €
22 €



EU-291P NTC WIRED OUTSIDE TEMPERATURE SENSOR

Sensor dedicated for EU-L-9 controller

WG.03.0064

5902479662732

21 €



STT-230/2 THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28x1,5 screw thread, Stroke: 3,5 mm, Class: IP40. Opening time: under 5 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5
M28 x 1,5

WG.01.0050
WG.01.0051

5902479660691
5902479661490

34 €



STT-230/2 T THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28 x 1,5 screw thread, Class - IP45. Opening time: under 3,5 min. Stroke - 3,7mm, Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5
M28 x 1,5

WG.01.0053
WG.01.0054

5902479663630
5902479665597

24 €
27 €



STT-230/2 M THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 screw thread, Class - IP42. Opening time: under 4 min. to 3mm, Stroke - 5mm, Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5

WG.01.0052

5902479665108

24 €

EU-L-12 WIRED/WIRELESS CONTROLLER FOR THERMOSTATIC ACTUATORS (8 SECTIONS) WITH WIFI

Functions: the ability to handle max. 50 thermoelectric actuators, zones can be created using 8 dedicated wired regulators or wireless system regulators or temperature sensors, or wired temperature sensors C-7p:

- 3 zones with 3 outputs each (if there are more actuators, the maximum output load is 0,3A)
- 5 zones with 2 outputs each (if there are more actuators, the maximum output load is 0,3A)
- one 230V output for a pump
- voltage-free relay (to control an additional heating device)
- possibility of controlling wireless actuators STT-868/STT-869 (the maximum of 6 per zone)
- in each zone, it is possible to install up to 6 wireless EU-C-2n window opening sensors
- possibility of connecting 6 executive modules EU-MW-1 or EU-MW-1/230
- possibility of connecting EU-i-1 or EU-i-1m valve module
- **up to 4 EU-ML-12 slaves can be connected**
- the EU-M-12 control panel can be connected
- possibility to control the installation via the Internet, eModul application - EU-WiFi L module included
- heating/cooling function
- software update via USB
- **OpenTherm communication**

WG.20.0171

5902479664460

428 €

EU-ML-12 IS AN EXTENSION OF THE EU-L-12 SYSTEM

Functions: the device is not standalone controller, it has to be connected to the EU-L-12 - MASTER

- wired (RS 485) or wireless communication with the MASTER controller EU-L-12
- the ability to handle max. 50 thermoelectric actuators, zones can be created using 8 dedicated wired regulators or wireless system regulators or temperature sensors, or wired temperature sensors C-7p:
- 3 zones with 3 outputs each (if there are more actuators, the maximum output load is 0,3A)
- 5 zones with 2 outputs each (if there are more actuators, the maximum output load is 0,3A)
- one 230V output for a pump
- voltage-free relay (to control an additional heating device)
- possibility of controlling wireless actuators STT-868/STT-869 (the maximum of 6 per zone)
- in each zone, it is possible to install up to 6 wireless EU-C-2n window opening sensors
- possibility of connecting 6 executive modules EU-MW-1 or EU-MW-1/230
- possibility of connecting EU-i-1 or EU-i-1m valve module
- includes repeater function
- heating/cooling function
- software update via USB

WG.20.0169

5902479664477

391 €

ROOM REGULATORS AND SENSORS POWERED FROM MAIN CONTROLLER - DEDICATED RS 485

EU-R-X DEDICATED WIRED ROOM REGULATOR FOR EU-L-X WIFI CONTROLLER

Functions: room temperature control, additional control based on floor temperature (if floor sensor is used), RS485 wired communication **4-wire / no batteries**

Equipment: built-in room temperature sensor, LCD display, no backlight, mechanical buttons

5902479665627

48 €

EU-R-12b DEDICATED WIRED ROOM REGULATOR FOR EU-L-X WIFI CONTROLLER

Functions: room temperature control, additional control based on floor temperature (if floor sensor is used), RS485 wired communication **4-wire / no batteries**

Equipment: built-in room temperature sensor, humidity sensor, LCD display, no backlight

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0703

5902479664569

65 €

WG.11.0704

5902479664576

EU-R-12s DEDICATED WIRED ROOM REGULATOR FOR EU-L-X WIFI CONTROLLER

Functions: room temperature control, additional control based on floor temperature (if floor sensor is used), RS485 wired communication **4-wire / no batteries**

Equipment: built-in room temperature sensor, humidity sensor, LCD display with temporary backlight

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0705

5902479664545

78 €

WG.11.0706

5902479664552

EU-F-12b DEDICATED WIRED ROOM REGULATOR FOR EU-L-X WIFI CONTROLLER FOR 55MM FRAME SYSTEMS

Functions: room temperature control, additional control based on floor temperature (if floor sensor is used), RS485 wired communication **4-wire / no batteries**

Equipment: built-in room temperature sensor, humidity sensor, LCD display, no backlight, flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0735

5902479665573

61 €

WG.11.0736

5902479665610

TEMPERATURE SENSORS - WIRED

EU-C-7p WIRED ROOM TEMPERATURE SENSOR

Room temperature sensor

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.03.0072

5902479661032

22 €

WG.03.0075

5902479662060

ROOM REGULATORS AND TEMPERATURE SENSORS - BATTERY, WIRELESS

EU-C-8r WIRELESS ROOM TEMPERATURE SENSOR

Power: 2xAAA batteries

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.03.0079

5902479661056

38 €

WG.03.0082

5902479662084



TECH
CONTROLLERS



EU-C-8f WIRELESS FLOOR TEMPERATURE SENSOR

Floor temperature sensor NTC type, power supply: 2x AAA batteries

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WHILE STOCKS LAST

WG.03.0076
WG.03.0078

5902479661643
5902479662220

43 €



EU-C-mini WIRELESS ROOM TEMPERATURE SENSOR

Dimensions: 37mm x 37mm x 16mm

WHILE STOCKS LAST

WG.03.0085

5902479661636

37 €



EU-CL-mini WIRELESS ROOM TEMPERATURE SENSOR IN HERMETIC CASING

MEETS THE IP64 STANDARD

Dimensions: 44,3mm x 44,3mm x 17mm

WG.03.0084

5902479661636

43 €



EU-C-8zr WIRELESS OUTSIDE TEMPERATURE SENSOR

Power: 2xAAA batteries

WG.03.0083

5902479661063

39 €



EU-R-8b WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0188
WG.11.0192

5902479661070
5902479662091

49 €



EU-R-8x WIRELESS REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LCD display, 2xAA batteries, no backlit, mechanical buttons

5902479665924

48 €



EU-R-8b PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, temperature control on the basis of floor temperature (in case of using NTC floor sensor - not included), LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0195
WG.11.0196

5902479663647
5902479663654

66 €



EU-R-8s PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, 2xAAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0644
WG.11.0696

5902479664385
5902479664378

100 €



EU-R-8pb PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, powered 2xAAA batteries, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0699
WG.11.0700

5902479665009
5902479665016

108 €

ROOM REGULATORS - 230V, WIRELESS



EU-R-8z WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LED display, power supply: 230V 50Hz to 5V included

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0202
WG.11.0203

5902479661087
5902479662107

66 €



EU-F-8z WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR FOR 55MM FRAME SYSTEMS

Functions: room temperature control, heating program with time limit, additional control based on floor temperature (in case of using NTC floor sensor - not included),

Equipment: built-in room temperature and humidity sensor, LCD display, no backlit, 230V powered, Flush mountable in electrical box (ø60mm), no backlit,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0634
WG.11.0686

5902479664408
5902479664415

89 €



EU-R-8pz PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlight, powered 230V, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0701
WG.11.0702

5902479665023
5902479665030

136 €

ADDITIONAL MODULES AND ACTUATORS



EU-M-12/EU-M-12t UNIVERSAL CONTROL PANEL FOR EU-L-12 (FLUSH MOUNTABLE)

Functions: Zone registration, possibility of adjusting each zone parameters (Schedule settings, pre-set temperature), possibility of activating/deactivating a zone, setting time and date for the whole set, screensaver, alarm clock, screen lock, Communication with the EU-L-12 master controller can be wired (RS485) or wireless (WTP). Without built-in temperature sensor.

* White or black casing. In case of lack of colour selection color will be chosen randomly.

EU-M-12

WG.20.0170

5902479664484

WG.20.0193

5902479664491

EU-M-12T

WG.20.0188

5902479664521

WG.20.0189

5902479664538

303 €



EU-C-2N WINDOW SENSOR

Functions: wireless communication, window opening signal, heating control, compact in size, long-life battery, discreet design.

Power: EVE ER14250 S battery

RAL 9010 - white

WG.03.0070

5902479661339

RAL 7016 - antracite

WG.03.0069

5902479664248

RAL 8017 - brown

WG.03.0071

5902479664255

RAL 8003 - golden oak

WG.03.0068

5902479664262

45 €



EU-MW-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MW-1) or voltage relay (EU-MW-1-230V), operation in manual mode, wireless communication with main controller or temperature sensor (master/slave mode), in case of loss of communication, the contact is switched off 4 LEDs indicating: communication, power, manual mode, contact status

EU-MW-1

WG.05.0114

5902479661346

EU-MW-1-230V

WG.05.0116

5902479662374

114 €



EU-MWN-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MWN-1) or voltage relay (EU-MWN-1-230V), wireless communication with main controller (slave mode), in case of loss of communication, the contact is switched off

EU-MWN-1

WG.05.0197

5902479664507

EU-MWN-1 230V

WG.05.0117

5902479664392

114 €



EU-RP-4 SIGNAL REPEATER

The signal repeater is a small electronic device that increases the range of wireless communication between devices without the need for additional cables. Thanks to the device, controller which are away from main unit will be able to establish a stable connection

WG.05.0140

5902479662824

114 €



EU-G-X WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S p, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 EU-L-X WiFi, EU-L-12, controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAAA 1,5V batteries. new design, hidden registration button. **Available thread M28x1,5 adapter**

WG.12.0045

5902479665054

97 €



STT-869 WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S p, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAAA 1,5V batteries. new design, registration button built on the front of actuator, **Available thread M28x1,5 adapter**

WG.12.0016

5902479662381

97 €



EU-i-1m MIXING VALVE CONTROLLER (1 MIXING VALVE ACTUATOR) (EXPANSION MODULE FOR MAIN CONTROLLER)

Fuctions: control of the three- or four-way mixing valve, return water temperature protection, weather-based regulation, week-based regulation, the possibility of connecting room regulator with RS or traditional communication.

WG.05.0030

5902479661612

139 €



FLOOR TEMPERATURE SENSOR - NTC TYPE

(plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO

150cm

WG.01.0031

5902479661209

250cm

WG.01.0032

5902479664279

21 €

22 €



TECH
CONTROLLERS

**EU-291P NTC WIRED OUTSIDE TEMPERATURE SENSOR**

Sensor dedicated for EU-L-9 controller

WG.03.0064

5902479662732

21 €

**STT-230/2 T THERMOELECTRIC ACTUATOR****ACTUATOR IS NORMALLY CLOSED (NC).****Technical Data:** Fittings: nut with M30 x 1,5 or M28x1,5 screw thread, Stroke: 3,5 mm, Class: IP40. Opening time: under 5 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5

WG.01.0050

5902479660691

34 €

M28 x 1,5

WG.01.0051

5902479661490

**STT-230/2 T THERMOELECTRIC ACTUATOR****ACTUATOR IS NORMALLY CLOSED (NC).****Technical Data:** Fittings: nut with M30 x 1,5 or M28 x 1,5 screw thread, Class - IP45. Opening time: under 3,5 min. Stroke - 3,7mm,Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5

WG.01.0053

5902479663630

24 €

M28 x 1,5

WG.01.0054

5902479665597

27 €

**STT-230/2 M THERMOELECTRIC ACTUATOR****ACTUATOR IS NORMALLY CLOSED (NC).****Technical Data:** Fittings: nut with M30 x 1,5 screw thread, Class - IP42.. Opening time: under 4 min. to 3mm, Stroke - 5mm,Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5

WG.01.0052

5902479665108

24 €

HEATING CONTROLL
SYSTEMS**TECH**
CONTROLLERS

SAVE

25%

ON HEATING
WITH HEAT PUMP
OR OTHER HEAT SOURCES
WITH CONTROLLERS



WIRED ROOM REGULATORS two-state (ON/OFF)



EU-294 v1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, heating/cooling program with time limit, wired communication

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0144

5902479661018

WG.11.0147

5902479662053

42 €



EU-T-2.1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, humidity sensor, heating/cooling program with time limit, wired communication

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries,

WG.11.0642

5902479665085

65 €



EU-295 v3 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlit,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries

WG.11.0151

5902479661544

57 €



EU-297 v3 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlit,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0155

5902479662947

WG.11.0156

5902479662954

91 €



EU-297z v3 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlit, possibility of powering regulator from EU-L-5s controller

Equipment: built-in room temperature sensor, LCD display, 230V powered, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0158

5902479663746

WG.11.0604

5902479663753

100 €



EU-T-3.1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlit,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0160

5902479663906

WG.11.0601

5902479664217

88 €



EU-T-4.1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, weekly t, manual mode, day/night program, temporary display backlit, Optimum Start function, heating/cooling function, wired communication

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0693

5902479664590

65 €



EU-T-5z WiFi WIRED TWO-STATE ROOM REGULATOR WITH WIFI

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor EU-C-8f is used), temporary display backlit,

Equipment: wireless temperature sensor EU-C-mini included, LCD display, 230V powered, built-in WiFi module, Flush mountable in electrical box (ø60mm)

Maintain of the system via web app: www.emodul.eu

WG.20.0168

5902479665665

149 €



EU-292 v3 WIRED TWO-STATE ROOM REGULATOR (3MM GLASS)

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlit, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wired communication

Equipment: built-in room temperature sensor, front panel made of 3mm glass

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0137

5902479660257

WG.11.0139

5902479660264

82 €



EU-293 v3 WIRED TWO-STATE ROOM REGULATOR (1MM GLASS)

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlit, temperature control on the basis of floor temperature (in case of using floor sensor), Optimum Start function, heating/cooling function, wired communication, Flush mountable in electrical box (ø60mm)

Equipment: built-in room temperature sensor, front panel made of 1mm glass

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0142

5902479662886

WG.11.0143

5902479662893

104 €

WHILE STOCKS LAST



TECH
CONTROLLERS

**EU-293z v3 WIRED TWO-STATE ROOM REGULATOR (1MM GLASS)**

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlit, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wired communication, possibility of powering regulator from EU-L-5s controller

Equipment: built-in room temperature sensor, LCD display, 230V powered, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WHILE STOCKS LAST

WG.11.0645
WG.11.0697

5902479663791
5902479663807

124 €**WIRELESS ROOM REGULATORS two-state (ON/OFF)****EU-294 v2 WIRELESS TWO-STATE ROOM REGULATOR**

Functions: room temperature control, heating/cooling program with time limit,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0148
WG.11.0149

5902479661117
5902479662138

78 €**EU-T-2.2 WIRELESS TWO-STATE ROOM REGULATOR WITH HUMIDITY SENSOR**

Functions: room temperature control, humidity sensor, heating/cooling program with time limit, wireless communication

Equipment: built-in room temperature and humidity sensor, LCD display, 2xAAA Batteries, no backlit, set for wireless communication

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0595
WG.11.0596

5902479664040
5902479664057

90 €**EU-292 v2 WIRELESS TWO-STATE ROOM REGULATOR (3MM GLASS)**

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlit, temperature control on the basis of floor temperature (in case of using floor sensor), Optimum Start function, heating/cooling function

Equipment: built-in room temperature sensor, front panel made of 3mm glass, controller stand, set for wireless communication, possibility of external sensor readout (optional)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0135
WG.11.0136

5902479660233
5902479660240

142 €**EU-293 v2 WIRELESS TWO-STATE ROOM REGULATOR (1MM GLASS)**

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlit, temperature control on the basis of floor temperature (in case of using floor sensor), Optimum Start function, heating/cooling function, wireless communication, Flush mountable in electrical box (ø60mm)

Equipment: built-in room temperature sensor, front panel made of 1mm glass, set for wireless communication,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WHILE STOCKS LAST

WG.11.0140
WG.11.0141

5902479662886
5902479662893

178 €**EU-293z v2 WIRED TWO-STATE ROOM REGULATOR (1MM GLASS)**

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlit, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wireless communication,

Equipment: built-in room temperature sensor, LCD display, 230V powered, Flush mountable in electrical box (ø60mm), set for wireless communication,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WHILE STOCKS LAST

WG.11.0646

5902479663814
5902479663821

201 €**EU-295 v2 WIRELESS TWO-STATE ROOM REGULATOR**

Functions: room temperature control, day/night program, wireless communication, additional control based on floor temperature (if floor sensor is used), temporary display backlit,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries

WG.11.0150

5902479661537

122 €**EU-297 v2 WIRELESS TWO-STATE ROOM REGULATOR**

Functions: room temperature control, day/night program, heating/cooling function, wireless communication, additional control based on floor temperature (if floor sensor is used), temporary display backlit,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries, set for wireless communication, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WHILE STOCKS LAST

WG.11.0154
WG.11.0599

5902479662923
5902479662930

161 €**EU-297z v2 WIRELESS TWO-STATE ROOM REGULATOR**

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlit,

Equipment: built-in room temperature sensor, LCD display, 230V powered, Flush mountable in electrical box (ø60mm), set for wireless communication

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WHILE STOCKS LAST

WG.11.0157
WG.11.0602

5902479663760
5902479663777

171 €



EU-T-3.2 WIRELESS TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlight.

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries, set for wireless communication

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WHILE STOCKS LAST

WG.11.0159
WG.11.0643

5902479663890
5902479664200

159 €



EU-T-4.2 WIRELESS TWO-STATE ROOM REGULATOR

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlight, Optimum Start function, heating/cooling function, wireless communication

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries, set for wireless communication

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0733

5902479664613

121 €

WIRED ROOM REGULATORS WITH RS COMMUNICATION



EU-280 WIRED ROOM REGULATOR WITH RS COMMUNICATION

Functions: control of the room temperature, control of the central heating boiler temperature, control of the DHW temperature, control of the mixing valves temperature, outside temperature monitoring, weekly-based heating mode, alarm, parental lock, displaying current room and CH boiler temperatures, alarm history, software update via USB

Equipment: large, clear, colour touch 4,3"-LCD display, built-in room temperature sensor, power supply 12V DC RS communication cable for the boiler controller, USB port
Room regulator can operate only with TECH controllers equipped with RS communication: EU-37RS, EU-48, EU-480, EU-880zPID, EU-i-3, EU-i-2, EU-i-1, EU-i-1m, EU-i-1CWU,

WG.11.0109

5902479660325

252 €



EU-281 WIRED ROOM REGULATOR WITH RS COMMUNICATION (2MM GLASS)

Functions: control of the room temperature, control of the central heating boiler temperature, control of the DHW temperature, control of the mixing valves temperature, outside temperature monitoring, weekly-based heating mode, alarm, parental lock, displaying current room and CH boiler temperatures, alarm history, software update via USB

Equipment: large, clear, colour touch 4,3"-LCD display, built-in room temperature sensor, power supply 12V DC RS communication cable for the boiler controller, USB port
Room regulator can operate only with TECH controllers equipped with RS communication: EU-37RS, EU-48, EU-480, EU-880zPID, EU-i-3, EU-i-2, EU-i-1, EU-i-1m, EU-i-1CWU,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WHILE STOCKS LAST

WG.11.0116
WG.11.0120

5902479660332
5902479662039

255 €

WIRELESS ROOM REGULATORS WITH RS COMMUNICATION



EU-280 + EU-260 WIRELESS ROOM REGULATOR WITH RS COMMUNICATION

Functions: control of the room temperature, control of the central heating boiler temperature, control of the DHW temperature, control of the mixing valves temperature, outside temperature monitoring, weekly-based heating mode, alarm, parental lock, displaying current room and CH boiler temperatures, alarm history, software update via USB

Equipment: large, clear, colour touch 4,3"-LCD display, built-in room temperature sensor, power supply 12V DC RS communication cable for the boiler controller, USB port, set for wireless communication

Room regulator can operate only with TECH controllers equipped with RS communication: EU-37RS, EU-48, EU-480, EU-880zPID, EU-i-3, EU-i-2, EU-i-1, EU-i-1m, EU-i-1CWU,

WHILE STOCKS LAST

WG.11.0110

5902479660875

297 €



EU-281 C WIRELESS ROOM REGULATOR WITH RS COMMUNICATION (2MM GLASS, FLUSH-MOUNTABLE)

Functions: control of the room temperature, control of the central heating boiler temperature, control of the DHW temperature, control of the mixing valves temperature, outside temperature monitoring, weekly-based heating mode, alarm, parental lock, displaying current room and CH boiler temperatures, alarm history, software update via USB. Easy installation in a flush mounting box (ø60mm).

Equipment: large, clear, colour touch 4,3"-LCD display, built-in room temperature sensor, power supply 12V DC RS communication cable for the boiler controller, USB port, set for wireless operation, easy installation in an electrical box (ø60mm). Power supply: 230V 50Hz.

Room regulator can operate only with TECH controllers equipped with RS comon: EU-37RS, EU-48, EU-480, EU-880zPID, EU-i-3, EU-i-2, EU-i-1, EU-i-1m, EU-i-1CWU,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WHILE STOCKS LAST

WG.11.0118
WG.11.0119

5902479661162
5902479662145

330 €

ROOM REGULATORS FOR 55mm FRAME SYSTEMS



EU-F-2z v1 WIRED ROOM REGULATOR FOR 55mm FRAME SYSTEMS

Functions: control of the room temperature, heating/cooling, display autolock function,

Equipment: built-in room temperature sensor, LCD display with no backlight, power supply: 230V,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0609
WG.11.0636

5902479664095
5902479664132

75 €



EU-F-2z v2 WIRELESS ROOM REGULATOR FOR 55mm FRAME SYSTEMS

Functions: control of the room temperature, heating/cooling, display autolock function,

Equipment: built-in room temperature sensor, LCD display with no backlight, power supply: 230V, set for wireless communication,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0654
WG.11.0657

5902479664101
5902479664149

104 €



TECH
CONTROLLERS



F-4z v1 WIRED ROOM REGULATOR FOR 55mm FRAME SYSTEMS

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlight, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wired communication

Equipment: built-in room temperature sensor, front panel made of 3mm glass, 230V powered,
* White or black casing. In case of lack of colour selection color will be chosen randomly.

WHILE STOCKS LAST

WG.11.0633
WG.11.0687

5902479664118
5902479664156

101 €



F-4z v2 WIRELESS ROOM REGULATOR FOR 55MM FRAME SYSTEMS

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlight, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wireless communication

Equipment: built-in room temperature sensor, front panel made of 3mm glass, power supply: 230V, set for wireless communication,
* White or black casing. In case of lack of colour selection color will be chosen randomly.

WHILE STOCKS LAST

WG.11.0628
WG.11.0689

5902479664125
5902479664163

178 €

REGULATORS FOR GAS BOILERS



EU-2801 WiFi ROOM REGULATOR WITH OPENTHERM COMMUNICATION + WIFI COMMUNICATION

Functions: smart maintaining the room set temperature, smart control of the CH boiler set temperature, changing the room set temperature basing on the outside temperature (weather-based control), outside temperature view, weekly-based heating program for room and boiler, displaying alarms from heating device, acces to temperature charts of heating device, alarm clock, parental lock, **WiFi communication**, **Maintain of the system via web app: www.emodul.eu**

Equipment: large, clear, colour-touchscreen, built-in room sensor, flush-mountable
* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0114
WG.11.0115

5902479661377
5902479662183

410 €



EU-WiFi OT ROOM REGULATOR WITH OPENTHERM COMMUNICATION + WIFI COMMUNICATION

Functions: smart maintaining the room set temperature, smart control of the CH boiler set temperature, changing the room set temperature basing on the outside temperature (weather-based control), outside temperature view, weekly-based heating program for room and boiler, displaying alarms from heating device, acces to temperature charts of heating device, alarm clock, **WiFi communication**, **Maintain of the system via web app: www.emodul.eu**

Equipment: large screen, built-in room sensor, in set additional wireless temperature sensor **EU-R-8b** and wired outdoor temperature sensor **EU-291p NTC**
* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0108

5902479662909

236 €

AIR CLEANING AND STERILIZING



OTS-15 OZONE GENERATOR 15g/h - ADJUSTABLE

Function: Ozone generator is designed for ozonation of all types of rooms, flats, cars and cargo spaces or air conditioning systems. The device is also intended for home use, office space and a range of other places such as a beauty salon or a dentist's office where disinfection of rooms is required. The ozone generator may also be used to disinfect and deodorise rooms. It is important to remember that during ozonation, people or animals are not allowed to stay in the room. **Programmable device operation time - the operation time can be adjusted to the size of the room (specifying the room dimensions), or set manually.**

Technical data: maximum performance: **up to 15 000 mg/h**, Method of ozone production: corona discharge, Fan capacity: 165 (±10%) m³/h, power consumption: 110W
fuse: 1.6A, ambient operating temperature: 5-50°C, acceptable relative ambient humidity: <80% REL.H, weight: 2.7 kg, cable length: 1.5 m

WG.13.0032

5902479663708



OTS-30 OZONE GENERATOR 30g/h - ADJUSTABLE

Function: Ozone generator is designed for ozonation of all types of rooms, flats, cars and cargo spaces or air conditioning systems. The device is also intended for home use, office space and a range of other places such as a beauty salon or a dentist's office where disinfection of rooms is required. The ozone generator may also be used to disinfect and deodorise rooms. It is important to remember that during ozonation, people or animals are not allowed to stay in the room. **Programmable device operation time - the operation time can be adjusted to the size of the room (specifying the room dimensions), or set manually.**

Technical data: maximum performance: **up to 30 000 mg/h**, Method of ozone production: corona discharge, Fan capacity: 230 (±10%) m³/h, power consumption: 220W
fuse: 1.6A, ambient operating temperature: 5-50°C, acceptable relative ambient humidity: <80% REL.H, weight: 3.2 kg, cable length: 1.5 m

WG.13.0033

5902479663715



SPT-31 INOX AIR STERILISER - ADJUSTABLE

Function: The main task of SPT-31 INOX is to eliminate bacteria, viruses, mould, fungi and other substances which are harmful to the body. The device uses UV radiation in order to effectively disinfect the air in a room. Thanks to the use of appropriate technology and wavelength, it is possible to conduct air sterilization on an ongoing basis without the need to leave the room. For this purpose, the device has been equipped with specialized lamps without the wavelength range of 100-230 nm, thanks to which they do not emit ozone. The air steriliser can be successfully used in offices, beauty salons, shops or homes.

Technical data: maximum power: 75W, standby power: 1.7W, **lamp power: 15W (in lamp 2x15W)**, type of lamp: Philips TUV T8 15W G15, lifespan: 9000 hours, **radiation: UV-C 253,7 nm wavelength**, **maximum air flow capacity: up to 260 m³/h**, maximum noise level: 44dB, device dimension: 145x295x625mm, filter dimensions: 255x135x10mm

WG.13.0004

5902479664620



AUV UV FLOW-THROUGH LAMP FOR WATER

Function: The UV flow-through lamp uses ultraviolet radiation with a UV-C wavelength, which destroys the DNA of microorganisms such as bacteria, viruses, and protozoa. This makes the water safe for drinking and household use, eliminating the risk of waterborne diseases.

Technical Data:

With Controller:

AUV-2.71 S : flow rate 2.71m³/h, power 41 W

AUV-1.81 S: flow rate 1.81m³/h, power 28 W

AUV-1.36 S: flow rate 1.36m³/h, power 21 W

Without Controller:

AUV-2.71 : flow rate 2.71m³/h, power 41 W

AUV-1.81: flow rate 1.81m³/h, power 28 W

AUV-1.36: flow rate 1.36m³/h, power 21 W

AUV-0.2 flow rate 0.2m³/h, power 8 W

AUV-2.71 S

WG.13.0102

5902479666334

453 €

AUV-1.81 S

WG.13.0110

5902479666341

417 €

AUV-1.36 S

WG.13.0111

5902479666358

392 €

AUV-2.71

WG.13.0112

5902479666365

331 €

AUV-1.81

WG.13.0113

5902479666372

261 €

AUV-1.36

WG.13.0114

5902479666389

224 €

AUV-0.2

WG.13.0115

5902479666396

112 €

INSTALLATION CONTROLLERS



EU-27i INSTALLATION CONTROLLER (2 PUMPS)

Functions: CH pump control, control of additional DHW or floor pump, anti-stop function, anti-freeze function

Equipment: LCD display, CH temperature sensor, additional pump temperature sensor.

WG.14.0058

5901445470319

92 €



EU-427i INSTALLATION CONTROLLER (3 PUMPS)

Functions: time-based or temperature-based control of the three pumps, anti-stop function, anti-freeze function, the possibility of setting any pump priorities, possibility of connecting a room regulator with traditional communication (a two-state regulator – ON/OFF)

Equipment: LCD display, three temperature sensors

WG.14.0065

5901445470364

129 €



EU-513 INPUTS INTEGRATOR - 5

Functions: Integration of 5 voltage inputs, control of one 230V output

WG.05.0027

5902479661414

67 €



EU-517 2 HEATING CIRCUITS MODULE

Functions: control of two pumps, cooperation with two room regulators with traditional communication (on/off), control of potential free contact

WG.05.0158

5902479661230

65 €



EU-i-1m MIXING VALVE CONTROLLER (1 MIXING VALVE ACTUATOR) (EXPANSION MODULE FOR MAIN CONTROLLER)

Functions: control of the three- or four-way mixing valve, return water temperature protection, weather-based regulation, week-based regulation, the possibility of connecting room regulator with RS or traditional communication.

WG.05.0030

5902479661612

139 €



EU-i-1 MIXING VALVE CONTROLLER (1 MIXING VALVE ACTUATOR)

Functions: control of the three- or four-way mixing valve, valve pump control, the possibility of controlling two valves by means of additional i-1 or i-1m modules, return water temperature protection, weather-based regulation, week-based regulation, the possibility of connecting room regulator with RS or traditional communication, the possibility of connecting EU-505 Ethernet/EI-WiFi RS module. USB port for software update [Maintenance via emodul app](#)

Equipment: LCD display, mixing valve temperature sensor, return water temperature sensor, tank temperature sensor, external sensor.

WG.14.0067

5902479661698

191 €



EU-i-1 DHW MIXING VALVE CONTROLLER (1 MIXING VALVE ACTUATOR + DHW)

Functions: control of the three- or four-way mixing valve, valve pump control, DHW pump control, the possibility of controlling two valves by means of additional i-1 or i-1m modules, return water temperature protection, weather-based regulation, week-based regulation, the possibility of connecting room regulator with RS or traditional communication, the possibility of connecting EU-505 Ethernet/EI-WiFi RS module. USB port for software update [Maintenance via emodul app](#)

Equipment: LCD display, mixing valve temperature sensor, return water temperature sensor, DHW temperature sensor, external sensor.

WG.14.0068

5902479661674

201 €



EU-i-2 PLUS INSTALLATION CONTROLLER WITH OPENTHERM (2 MIXING VALVE ACTUATORS)

Functions: Possibility of control heating device with OpenTherm, smooth control of the two mixing valves, two mixing valve pumps, DHW pump control, two configurable voltage-free outputs, two configurable voltage outputs, return water temperature protection. Weather-based and week-based regulation. Possibility of connecting three room regulators with standard communication (two-state, on/off). Possibility of connecting room regulator with RS communication (overview and edition of temperatures from main controller). The possibility of controlling two valves by means of additional i-1, i-1m, modules. the possibility of connecting EU-505 Ethernet/EI-WiFi RS modules, 2 outputs 0-10 V. [Maintenance via emodul app](#)

Equipment: colour LCD 4,3" touchscreen, 6 temperature sensors for any configuration, external sensor,

WG.14.0164

5902479665061

365 €



EU-i-3 PLUS INSTALLATION CONTROLLER WITH OPENTHERM (3 MIXING VALVE ACTUATORS + SOLAR INSTALLATION)

Functions: Possibility of control heating device with OpenTherm, smooth control of the three mixing valves, three mixing valve pumps, DHW pump control, two configurable voltage-free outputs, two configurable voltage outputs, maintenance simply solar installation, return water temperature protection. Weather-based and week-based regulation. Possibility of connecting three room regulators with standard communication (two-state, on/off). Possibility of connecting room regulator with RS communication (overview and edition of temperatures from main controller). The possibility of controlling two valves by means of additional i-1, i-1m modules. the possibility of connecting EU-505 Ethernet/EI-WiFi RS modules, 2 outputs 0-10 V, PWM signal. [Maintenance via emodul app](#)

Equipment: colour LCD 4,3" touchscreen, 6 temperature sensors for any configuration, external sensor, collector sensor (PT-1000)

WG.14.0072

5902479661803

462 €



TECH
CONTROLLERS



EU-RI-1 WIRED ROOM REGULATOR WITH RS COMMUNICATION EU-I-2 OR EU-I-3 PLUS

Functions: room temperature control, day/night program, RS communication, temporary display backlight, work with installation controller EU-I-2, EU-I-3 (with new firmware) and EU-I-3 PLUS

Equipment: built-in room temperature sensor, LCD display,

WG.11.0216

5902479663678

75 €



EU-11 DHW CIRCULATION REGULATOR

Functions: controlling circulating pump operation, monitoring the pre-set temperature in a heating circuit, smart control of the circulation system, protection against overheating (DHW pump activation), anti-stop function, adjustable pump operation time

Principle of operation: DHW circulation regulator is intended for controlling DHW circulation to suit individual user's needs. In an economical and convenient way, it reduces the time needed for hot water to reach the fixtures. It controls the circulating pump which, when the user draws water, accelerates the flow of hot water to the fixture, exchanging the water there for hot water at the desired temperature in the circulation branch and at the tap. The system monitors the temperature set by the user in the circulation branch and it activates the pump only when the pre-set temperature drops. Thus it does not generate any heat loss in the DHW system. It saves energy, water and equipment in the system (e.g. circulation pump).

WG.14.0043

5902479661704

232 €

SOLAR INSTALLATION CONTROLLERS



EU-401N PWM SOLAR INSTALLATION CONTROLLER

Functions: control of the solar pump using PWM signal, supervision and handling of the solar system operation, protection against overheating and freezing of the collector, voltage-free output, the possibility of connecting EU-505 Ethernet/EU-WiFi RS modules.

Equipment: large, clear LCD display, collector temperature sensor, heat accumulator temperature sensor.

WG.19.0013

5902479662411

170 €



EU-402N PWM SOLAR INSTALLATION CONTROLLER

Functions: control of the solar pump using PWM signal, control of the pumps (or the pump and the valve), the possibility of connecting additional device: circulation pump, electric heater or sending a signal to the CH boiler to fire it up, supervision and handling of the solar system operation using 17 possible configurations of the system, protection against overheating and freezing of the collector, the possibility of connecting EU-505 Ethernet/EU-WiFi RS modules.

Equipment: large, clear LCD display, two collector temperature sensors, two heat accumulator temperature sensors

WG.19.0015

5901445470562

197 €

PUMP CONTROLLERS



EU-19 PUMP CONTROLLER

Functions: CH pump control, anti-stop function.

Equipment: CH temperature sensor, potentiometer to adjust the set temperature

WG.14.0044

5901445470005

40 €



EU-20 PUMP CONTROLLER

Functions: CH pump control

Equipment: CH temperature sensor, potentiometer to adjust the set temperature

WG.14.0045

5901445470012

39 €



EU-21 PUMP CONTROLLER

Functions: CH pump control, possible operation as a thermostat, anti-stop function, anti-freeze function.

Equipment: CH temperature sensor, LED display

WG.14.0048

5901445470142

54 €



EU-21 R PUMP CONTROLLER

Functions: CH pump control, possible operation as a thermostat, anti-stop function, anti-freeze function, voltage-free contact

Equipment: CH temperature sensor, LED display

WG.14.0170

5901445470753

61 €



EU-21 DHW PUMP CONTROLLER

Functions: DHW pump control, anti-stop function, anti-freeze function, potential-free output control, delta of DHW and CH temperatures to set, protection against DHW tank freezing

Equipment: 2x temperature sensor, LED display

WG.14.0048

5901445470654

82 €



EU-21 BUFFER PUMP CONTROLLER

Functions: buffer pump control, anti-stop function, anti-freeze function, potential-free output control, protection against buffer tank freezing

Equipment: 2x temperature sensor, LED display

WG.14.0047

5901445470661

82 €

CHARGING BOILER CONTROLLERS



EU-22 SIGMA CHARGING BOILER CONTROLLERS

Functions: control of the fan and CH pump, in SIGMA version (slower fan operation when the central heating approaches the set temperature)

Equipment: CH temperature sensor, LED display, temperature protection, additional stand for easy installation on the boiler.

WG.21.0060

5901445470920

108 €



EU-24 SIGMA CHARGING BOILER CONTROLLERS

Functions: control of the fan and CH pump-, in SIGMA version (slower fan operation when the central heating approaches the set temperature)

Equipment: CH temperature sensor, LED display, temperature protection.

WG.21.0063

5901445470937

113 €



EU-28n CHARGING BOILER CONTROLLERS

Functions: control of the fan, CH pump, DHW pump control, the possibility of connecting two-state room regulator (on/off),

Equipment: CH temperature sensor, DHW temperature sensor, LCD display, temperature protection

WG.21.0131

5901445470104

140 €



EU-28n zPID CHARGING BOILER CONTROLLER

Functions: automatic control of the fan operation, CH and DHW pumps control, zPID software (smart settings for operating parameters)

Equipment: LCD display, CH temperature sensor, DHW temperature sensor, flue gas sensor, temperature protection.

WG.21.0070

5901445470289

207 €



EU-81 CHARGING BOILER CONTROLLER

Functions: control of the fan, CH pump, DHW pump control, the possibility of connecting two-state room regulator (on/off)

Equipment: CH temperature sensor, DHW temperature sensor, LCD display, controller in metal casing for installation on the boiler

WG.21.0076

5901445470265

165 €



EU-81 zPID CHARGING BOILER CONTROLLER

Functions: automatic control of the fan operation, CH and DHW pumps control, zPID software (smart settings for operating parameters)

Equipment: LCD display, CH temperature sensor, DHW temperature sensor, flue gas sensor, temperature protection

WG.21.0085

5901445470302

228 €



EU-880 zPID CHARGING BOILER CONTROLLER

Functions: automatic control of the fan operation, CH, DHW and additional pumps control, mixing valve control, possibility of connecting room regulator with RS communication (preview and edition of boiler parameters) or two-state room regulator (on/off), possibility of connecting and EU-505/EU-WiFi RS Ethernet module. Possibility of controlling two additional mixing valves using EU-i1m, EU-i-1 modules, zPID software (smart settings for operating parameters).

Equipment: large graphic display facilitating the controller operation, knob of impulse generator, CH, DHW, mixing valve, return water, and flue gas sensors, external wireless sensor, power supply cable for controller and pumps, temperature protection, single-module panel casing for installation on the boiler, controller in metal casing obudowie nakotłowej

WG.21.0092

5902479660004

405 €

BOILER WITH FEEDER CONTROLLERS



EU-37n RS BOILER WITH FEEDER CONTROLLER

Functions: control of the fan and feeding screw or piston feeder (EU- 37n RS H), CH and DHW pumps control, the possibility of connecting EU-505 Ethernet/EU-WiFi RS modules (*RS option), the possibility of controlling two valves by means of additional EU-i-1m, EU-i-1 modules, the possibility of connecting room regulator with RS or traditional communication, weekly control (optional).

Equipment: LCD display, CH and DHW temperature sensor, feeder temperature sensor (protection), temperature protection, panel casing for installation on the boiler

WG.17.0061

5902479661834

260 €

version EU-37n RS H

WG.17.0064

5902479661841

EU-480 N BOILER WITH FEEDER CONTROLLER

Functions: control of the fan and feeding screw or piston feeder (EU- 480 H), CH, DHW, floor and circulation pumps control, control of the mixing valve, the possibility of connecting room regulator with RS or traditional communication, the possibility of connecting EU-505 Ethernet/EU-WiFi RS modules, the possibility of controlling two valves by means of additional EU-i-1m modules

Equipment: large graphic display facilitating the controller operation, knob of impulse generator, CH, DHW, mixing valve, return water, and flue gas sensors, external wireless sensor, power supply cable for controller and pumps, temperature protection, single-module panel casing for installation on the boiler, controller in metal casing

WG.17.0423

5902479662565

507 €

version EU-480 H

WG.17.0071

5902479661179

FIREPLACE CONTROLLERS



EU-391 zPID FIREPLACE CONTROLLER (COLOUR SCREEN, TOUCH BUTTONS)

Functions: control of the circulation pump, control of the additional pump, DHW pump or floor pump, buffer pump control or laddomat control, throttle control, a contactor switching the gas boiler on and of, depending on the desired circuit water temperature minus hysteresis, zPID software, buffer maintenance (two sensors), the possibility of connecting EU-505 Ethernet/EU-WiFi RS modules. **Maintenance via emodul app**

Equipment: flue gas sensor, floor, DHW, CH, top and bottom buffer sensors, throttle 100mm (for an extra charge 120 or 150mm), colour screen

ø100

WG.10.0033

5902479660646

373 €

ø120

WG.10.0034

5902479662589

385 €

ø150

WG.10.0035

5902479662596

398 €



EU-392 zPID FIREPLACE CONTROLLER (COLOUR, TOUCHSCREEN)

Functions: control of the circulation pump, control of the additional pump, DHW pump or floor pump, buffer pump control or laddomat control, throttle control, a contactor switching the gas boiler on and of, depending on the desired circuit water temperature minus hysteresis, zPID software, buffer maintenance (two sensors), the possibility of connecting EU-505 Ethernet/EU-WiFi RS modules. **Maintenance via emodul app**

Equipment: flue gas sensor, floor, DHW, CH, top and bottom buffer sensors, throttle 100mm (for an extra charge 120 or 150mm), colour touchscreen

ø100

WG.10.0051

5902479660639

398 €

ø120

WG.10.0052

5902479662602

410 €

ø150

WG.10.0053

5902479662619

423 €



THROTTLE

Available diameters: 100mm, 120mm, 150mm

ø100

WG.10.0002

5902479661247



ø120

WG.10.0006

5902479662473



ø150

WG.10.0009

5902479662480



TECH
CONTROLLERS

ADDITIONAL MODULES / ACCESSORIES



EU-MW-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MW-1) or voltage relay (EU-MW-1-230V), operation in manual mode, wireless communication with main controller or temperature sensor (master/slave mode), in case of loss of communication, the contact is switched off LEDs indicating: communication, power, manual mode, contact status

EU-MWN-1
EU-MWN-1-230V

WG.05.0114
WG.05.0116

5902479661346
5902479662374

114 €



EU-MWN-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MWN-1) or voltage relay (EU-MWN-1-230V), wireless communication with main controller (slave mode), in case of loss of communication, the contact is switched off

EU-MWN-1
EU-MWN-1-230V

WG.05.0197
WG.05.0117

5902479664507
5902479664392

114 €



EU-RP-4 SIGNAL REPEATER

The signal repeater is a small electronic device that increases the range of wireless communication between devices without the need for additional cables. Thanks to the device, controller which are away from main unit will be able to establish a stable connection

WG.05.0140

5902479662824

114 €



EU-67 PELLET LEVEL SENSOR

EU-67 sensor is intended for measuring the level of solid biofuels (pellet, oat, maize, etc.) not only in central heating boilers' tanks but also in grain silos, where the max. spacing between measuring sensors is not greater than 3,5m. To have a successful measurement it is necessary to deliver only dry fuel. Main principle of operation of the device is based on setting the level of biofuel using properly installed capacitive sensors.

WG.03.0102

5901445470425

339 €



EU-505 INTERNET MODULE

Functions: remote control of the floor heating system, control of the set temperature in each zone, possibility of define the schedules, preview the temperatures history for each zone, possibility of personalization the main screen, alarms notifications via e-mail.

Equipment: power supply: 5V DC, T-connector for RS, RS communication cable for main controller.

WG.05.0025

5902479660578

221 €



EU-WiFi RS WIFI INTERNET MODULE (WIFI CONNECTION)

Functions: Same as in EU-505. Internet connection via WiFi signal

WG.05.0040

5902479660974

237 €



STZ-120 T MIXING VALVE ACTUATOR

Functions: The actuator with 3-point signal control in 230V AC (50 Hz). manual mode, It comes with 1,5m cable, rotation time: 120 sec, adapters in set for: ESBE, Afriso, Herz, Womix, Honeywell, Wita.

WG.12.0046

5902479663739

135 €



STZ-180 RS MIXING VALVE ACTUATOR

Functions: The STZ-180 actuator is used to control three-way and four-way mixing valves. It is controlled by a 3-point signal and has a 180s rotation time. The actuator can be manually operated using a retractable handle. The set includes a temperature sensor and a voltage-free contact for controlling the pump operation. There is a display indicating the current temperature, set temperature, and percentage of valve opening. The RS power supply is included in the set. The actuator comes with adapters and mounting screws for valves from companies such as ESBE, Afriso, Herz, Womix, Honeywell, and Wita.

WG.12.0047

5902479663739

152 €



G-X WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S p, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAA 1,5V batteries. **Available thread M28x1,5 adapter**

WG.12.0045

5902479665054

97 €



STT-869 WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S p, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAA 1,5V batteries. new design, registration button built on the front of actuator, **Available thread M28x1,5 adapter**

WG.12.0016

5902479662381

97 €



STI-400 INVERTER

An inverter is a controller that allows devices (usually boilers) to continue working in the event of a power outage. It works similarly to typical UPS devices, but instead of using cells, the energy is stored in a battery. When the target device is connected to the inverter and we have access to grid power, the device is powered directly from the grid while the battery is kept in standby mode. In the event of a power outage, the controller switches to inverter mode, meaning the energy stored in the battery is converted to 230V and the device can continue to operate. The controller works with two types of batteries, gel and acid. Separate (although very similar) maintenance algorithms are written for each type.

Input: - 230V AC x1 - 12VDC x1, Output: - AC230V AC x1, Power: 400W

WG.13.0106

5902479665993

1075 €



THREAD ADAPTER FOR Wireless electric actuator STT-868 or STT-869

DANFOSS RAN > M30x1,5 >

WG.01.0048

5902479661872

12 €



THREAD ADAPTER FOR Wireless electric actuator STT-868 or STT-869

DANFOSS RTD-N > M30x1,5 >

WG.01.0049

5902479661889

12 €



THREAD ADAPTER FOR Wireless electric actuator STT-868 or STT-869

VALVEX > M30x1,5 >

WG.12.0003

5902479662756

12 €



THREAD ADAPTER FOR Wireless electric actuator STT-868 or STT-869

PINTOSI > M26x1,5 >

WG.12.0002

5902479662763

12 €



THREAD ADAPTER FOR Wireless electric actuator STT-868 or STT-869

COMAP/HERZ > M30x1,5 >

WG.12.0001

5902479662770

12 €



EU-260 SET FOR WIRELESS RS COMMUNICATION

Set for a wireless RS communication used in addition to room regulator consists of two modules:
V1 module is dedicated to the controller with RS communication and own power supply.
V2 Module is dedicated to the controller with RS communication without own power supply (e.g. EU-280).
An example application may also be communication between EU-505 Ethernet with the main CH boiler controller.

WG.05.0023

5902479660158

86 €



EU-262 SET FOR WIRELESS COMMUNICATION

Wireless communication set for two-state room regulators.

WG.05.0024

5902479660165

84 €



RS splitter

WG.05.0147

5902479661506

14 €



RS splitter RS-8

8 RS outputs

WG.05.0203

5902479665078

35 €



2-POLE CONTACTOR WITH PROTECTION

Appliance: Control one- or multipole electrical devices. Major application is to control heating systems, motors or pumps.
Rated current: 20 A, Coil supply voltage: 230 V AC (50 Hz), Maximum coil current consumption: 8 VA, Maximum coil load: up to 4kW (depending on the applied protection)
The set includes: contactor, fuse, wiring (power supply, male and female plugs)

5902479661513

128 €

ADDITIONAL SENSORS



EU-291P KTY WIRED OUTSIDE TEMPERATURE SENSOR

Sensor dedicated for controllers equipped with mixing valve control
e.g. EU-430, i-1, i-1m, EU-880 zPID, EU-480

WG.03.0063

5902479660899

21 €



EU-291P NTC WIRED OUTSIDE TEMPERATURE SENSOR

Sensor dedicated for EU-L-9 controller

WG.03.0064

5902479662732

21 €



FLOOR TEMPERATURE SENSOR - NTC TYPE

(plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO

150cm
250cm

WG.01.0031

5902479661209

21 €

WG.01.0032

5902479664279

22 €



SEMICONDUCTOR TEMPERATURE SENSOR - KTY TYPE

(plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO
Resistance at 25°C: 2kΩ, Coefficient: 0.79 %/K, Accuracy : 1%, Range of operation: -25÷90°C

150cm
150cm with plug
250cm
250cm with plug

WG.01.0025

5902479660905

21 €

WG.01.0026

5902479664286

22 €

WG.01.0027

5902479664293

22 €

WG.01.0028

5902479664309

23 €



SEMICONDUCTOR TEMPERATURE CLIP-ON SENSOR - KTY TYPE

(plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO
Resistance at 25°C: 2kΩ, Coefficient: 0.79 %/K, Accuracy : 1%, Range of operation: -25÷90°C

150cm
250cm

WG.01.0029

5902479663685

21 €

WG.01.0030

5902479664316

22 €



TECH
CONTROLLERS



BIMETALLIC SENSOR – (THERMAL OVERLOAD RELAY)

(plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO
Activation temperature 85°C, Accuracy: +/-3°C, Application: temperature protection

WG.01.0040

5902479660912

21 €



SEMICONDUCTING TEMPERATURE SENSOR FOR SOLAR SYSTEM- PT1000 TYPE

(silicone cable insulation) 1,5m
Resistance at 0°C: 1kΩ, Accuracy: +/-0.3°C, Range of operation: -25÷180°C

WG.01.0034

5902479661391

34 €



SEMICONDUCTING TEMPERATURE SENSOR FOR WATER TANK- PT1000 TYPE (FOR SOLAR SYSTEMS)

cable length 1,5m
Resistance at 0°C: 1kΩ, Accuracy: +/-0.3°C, Range of operation: -25÷95°C

WG.01.0033

5902479660929

23 €



FLUE GAS TEMPERATURE SENSOR - PT1000 TYPE

(cable insulation made of glass fiber)
Resistance at 0°C: 1kΩ, Accuracy: +/-0.3°C, Range of operation: -25÷480°C

WG.01.0035

5902479660936

64 €

30 cm
30cm with plug

WG.01.0036

5902479664323

65 €



PHOTOCELL – FIRE SENSOR

(plastified PVC cable insulation) 0,25m
Application: pellet-fired boilers

WG.01.0037

5902479660943

23 €



HALL GENERATOR (HALL'S SENSOR)

(plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO
Application: boilers with piston feeder

WG.01.0038

5902479660950

23 €

250cm



REED RELAY

(plastified PVC cable insulation) 2,5m - extra charge for each meter: 1 EUR NETTO
Application: boilers with piston feeder

WG.01.0039

5902479660967

23 €



SAFETY THERMOSTAT – (STB)

Activation temperature: 90÷110°C, Accuracy: +/-3÷5°C, Maximum current: 16A, Application: temperature protection

WG.01.0041

5902479661216

23 €



ANTENNA EXTENSION - SMA

SMA antenna cable for extending the antenna used in the L-8 controller, Cable length 5m. Cable type - coaxial, wave impedance - 50Ω, Cable / passage construction: SMA socket, SMA plug

WG.01.0047

5902479661520

20 €

FANS



STW-70 HMSK BLOWING FAN FOR CENTRAL HEATING BOILERS 25-50 KW

(Power consumption – 70W) old RV-12

T_000.00.000.00001

5902479660752



STW-60 EMSK BLOWING FAN FOR CENTRAL HEATING BOILERS UP TO 35 KW

(Power consumption – 60W) old RV-14

T_000.00.000.00002

5902479660769



WPA-117 BLOWING FAN FOR CENTRAL HEATING BOILERS

(Power consumption - 34 W)

T_000.00.000.00003

5901445470494



WPA-120 BLOWING FAN FOR CENTRAL HEATING BOILERS

(Power consumption - 83W / 75W)

T_000.00.000.00004

5902479661605



WPA-140 BLOWING FAN FOR CENTRAL HEATING BOILERS

(Power consumption - 100W)

T_000.00.000.00005

5901445470500



| Communication | Type | Name | Installation | | | Power supply | | | | Function | | | | | | | | | | Compatibility with system | | | | | | | | | | | | |
|---------------------------------------|-------------------------|---------------|----------------|-----------------|---------------|--------------|-----|-------------|----------------------|---------------------|------------------|-----------------|------------------------------|-----------------------|-----------------|---------------|------------------------|-------------------|----------|---------------------------|---------------------------------|--------|---------|---------|---------|---------|---------|--------------|-------------|-------------------|---|---|
| | | | wall mountable | flush mountable | frame systems | batteries | 24V | 230 V 50 HZ | from main controller | temperature set +/- | day / night mode | weekly schedule | temporary temp. change 0-24h | optional floor sensor | humidity sensor | Optimum Start | heating / cooling mode | display backlight | key lock | SINUM | WiFi-8s, WiFi-8s p, ST-16s WiFi | EU-L-4 | EU-L-5s | EU-L-7e | EU-L-8e | EU-L-9r | EU-L-10 | EU-L-4X WIFI | EU-L-X WIFI | EU-L-12 / EU-M-12 | | |
| Wired sensors and room thermostats | two-state | EU-294 v1 | * | | | * | | | | * | | | | | | | * | | | * | | | | | | | | | | | | |
| | | EU-295 v3 | * | | | * | | | | * | * | | | | * | | | | * | | * | | | | * | | | | | | | |
| | | EU-297 v3 | | * | | * | | | | * | * | * | | | * | | | * | * | * | * | | | | * | | | | | | | |
| | | EU-297z v3 | | * | | | | | * | ** | * | * | | | * | | | * | * | * | * | | | | * | | | | | | | |
| | | EU-T-2.1 | * | | | * | | | | | * | | | | | * | | * | * | * | * | | | | * | | | | | | | |
| | | EU-T-3.1 | * | | | * | | | | | * | | | | * | | | * | * | * | * | | | | * | | | | | | | |
| | | EU-T-4.1 | * | | | * | | | | | * | * | * | | | | * | * | * | * | * | | | | * | | | | | | | |
| | | EU-T-5z | | * | | | | | * | *** | * | * | * | | * | | | * | * | * | * | | | | * | | | | | | | |
| | | EU-292 v3 | * | | | * | | | | | * | * | * | | * | | | * | * | * | * | | | | * | | | | | | | |
| | | EU-293 v3 | | * | | * | | | | | * | * | * | | * | | | * | * | * | * | | | | * | | | | | | | |
| | | EU-293z v3 | | * | | | | | * | ** | * | * | * | | * | | | * | * | * | * | | | | * | | | | | | | |
| | | EU-F-2z v1 | | * | * | * | | | * | ** | * | | * | * | | * | | * | * | * | * | | | | * | | | | | | | |
| | | EU-F-4z v1 | | * | * | * | | | * | ** | * | * | * | * | * | * | * | * | * | * | * | | | | * | | | | | | | |
| | dedicated to the system | EU-R-9b | * | | | | | | | * | * | | * | * | * | | * | * | | | | | | | | | * | | | | | |
| | | EU-R-9s PLUS | * | | | | | | | * | * | | * | * | * | * | * | * | * | * | | | | | | | | * | | | | |
| | | EU-R-10b | * | | | | | | | * | * | | | * | | | | * | * | * | * | | | | | | | * | | | | |
| | | EU-R-10s PLUS | * | | | | | | | * | * | * | | * | | | | * | * | * | * | | | | | | | * | | | | |
| | | EU-R-X | * | | | | | | | * | * | | * | * | * | * | * | * | * | | | | | | | | | | * | * | * | * |
| | | EU-R-12b | * | | | | | | | * | * | | * | * | * | * | * | * | * | | | | | | | | | | * | * | * | * |
| | | EU-R-12s | * | | | | | | | * | * | | * | * | * | * | * | * | * | * | * | | | | | | | | * | * | * | * |
| | | EU-F-12b | | * | * | * | | | | * | * | | * | * | * | * | * | * | * | | | | | | | | | | * | * | * | * |
| | EU-C-7p | * | | | | | | | | | | * | * | | | | * | * | | | | * | | * | | * | | * | * | * | * | |
| | Sinum | R-S1 | | | | | | | | | | | | | | | | | | | | * | | | | | | | | | | |
| | | R-S2 | | | | | | | | | | | | | | | | | | | | * | | | | | | | | | | |
| | | R-S3 | | | | | | | | | | | | | | | | | | | | * | | | | | | | | | | |
| | | FR-S2 | | | | | | | | | | | | | | | | | | | | * | | | | | | | | | | |
| Wireless sensors and room thermostats | two-state | EU-294 v2 | * | | | * | | | | * | | | | | | | * | | | * | | | | | | | | * | | | | |
| | | EU-295 v2 | * | | | * | | | | | * | * | | | * | | | | * | * | * | | | | * | | | | * | | | |
| | | EU-297 v2 | | * | | * | | | | | * | * | | | * | | | * | * | * | * | | | | * | | | | * | | | |
| | | EU-297z v2 | | * | | | | | * | | * | * | | | * | | | * | * | * | * | | | | * | | | | * | | | |
| | | EU-T-2.2 | * | | | * | | | | | * | | | | | | | * | * | * | * | | | | * | | | | * | | | |
| | | EU-T-3.2 | * | | | * | | | | | * | * | | | * | | | * | * | * | * | | | | * | | | | * | | | |
| | | EU-T-4.2 | * | | | * | | | | | * | * | * | | | | * | * | * | * | * | | | | * | | | | * | | | |
| | | EU-292 v2 | * | | | * | | | | | * | * | * | | * | | | * | * | * | * | | | | * | | | | * | | | |
| | | EU-293 v2 | | * | | * | | | | | * | * | * | | * | | | * | * | * | * | | | | * | | | | * | | | |
| | | EU-293z v2 | | * | | | | | * | | * | * | * | | * | | | * | * | * | * | | | | * | | | | * | | | |
| | | EU-F-2z v2 | | * | * | * | | | * | | * | | * | * | | * | | * | * | * | * | | | | * | | | | * | | | |
| | | EU-F-4z v2 | | * | * | * | | | * | | * | * | * | * | * | * | * | * | * | * | * | | | | * | | | | * | | | |
| | dedicated to the system | EU-R-8b | * | | | * | | | | | * | | * | * | * | * | * | * | | * | * | * | * | * | | | * | * | * | * | * | * |
| | | EU-R-8X | * | | | * | | | | | * | | * | * | * | * | * | * | * | * | * | * | * | * | | | * | * | * | * | * | * |
| | | EU-R-8b PLUS | * | | | * | | | | | * | | * | * | * | * | * | * | * | * | * | * | * | * | | | * | * | * | * | * | * |
| | | EU-R-8s PLUS | * | | | * | | | | | * | | * | * | * | * | * | * | * | * | * | * | * | * | | | * | * | * | * | * | * |
| | | EU-R-8pb PLUS | | * | | * | | | | | * | | * | * | * | * | * | * | * | * | * | * | * | * | | | * | * | * | * | * | * |
| | | EU-R-8z | * | | | * | | | | | * | | * | * | * | * | * | * | * | * | * | * | * | * | | | * | * | * | * | * | * |
| | | EU-F-8z | | * | * | * | | | | | * | | * | * | * | * | * | * | * | * | * | * | * | * | | | * | * | * | * | * | * |
| | | EU-R-8pz PLUS | | * | | * | | | | | * | | * | * | * | * | * | * | * | * | * | * | * | * | | | * | * | * | * | * | * |
| | | EU-C-8r | * | | | * | | | | | * | | * | * | * | * | * | * | * | * | * | * | * | * | | | * | * | * | * | * | * |
| | | EU-C-8f | * | | | * | | | | | * | | * | * | * | * | * | * | * | * | * | * | * | * | | | * | * | * | * | * | * |
| | | EU-C-mini | * | | | * | | | | | * | | * | * | * | * | * | * | * | * | * | * | * | * | | | * | * | * | * | * | * |
| | | EU-CL-mini | * | | | * | | | | | * | | * | * | * | * | * | * | * | * | * | * | * | * | | | * | * | * | * | * | * |
| | | EU-C-8zr | * | | | * | | | | | * | | * | * | * | * | * | * | * | * | * | * | * | * | | | * | * | * | * | * | * |

* - function performed by the master controller to which the controller or sensor is connected ** - concerns only the connection of the regulator's power supply from the L-5s controller





TECH
CONTROLLERS

ul. Biała Droga 31, 34-122 Wieprz
tel. +48 33 330 00 07 | fax. +48 33 845 45 47
poczta@techsterowniki.pl | www.controllers.com

03/2024

